

# NPC CREDIT TRANSFER SCHEME CUSTOMER-TO-PSP RECOMMENDED IMPLEMENTATION GUIDELINES

NPC003-01 / 2023 Version 1.3 / Date issued: 27 November 2023 / Date effective: 27 November 2023

**Public**



Nordic Payments Council – Company Registration Number 802524-8645 – Box 7306 – SE 103 94 Stockholm

© 2023 Copyright Nordic Payments Council (NPC)

Based on EPC132-08 SEPA Credit Transfer Scheme Customer-to-PSP Implementation Guidelines 2023 with the authorisation from

Conseil Européen des Paiements AISBL – Enterprise N° 0873.268.927 – Cours Saint-Michel 30 – B 1040 Brussels

© 2022 Copyright European Payments Council (EPC) AISBL

Reproduction for non-commercial purposes is authorized, with acknowledgement of the source

## Abstract

This document sets out the recommended rules for implementing the 2023 NPC Credit Transfer Scheme Rule-book based on version 2019 of the customer-to-PSP credit transfer ISO 20022 XML message standards.

## TABLE OF CONTENTS

<b>0. Document Information .....</b>	<b>3</b>
0.1 References .....	3
0.2 Change History .....	4
0.3 Purpose of Document .....	4
<b>1. Introduction .....</b>	<b>5</b>
1.1 Coverage of the NPC customer-to-PSP Implementation Guidelines .....	5
1.2 Use of these Guidelines by the instructing and instructed parties .....	6
1.3 Notation Conventions .....	7
1.4 Character Set.....	8
1.5 General Message Element Specifications .....	9
1.5.1 BIC .....	9
1.5.2 Currency .....	9
1.5.3 Alias and Proxy .....	9
1.5.4 Structured creditor references, e.g. OCR-references.....	9
1.5.5 Extended remittance information, up to 999 occurrences of structured references .....	10
1.6 Implementation of ISO 20022 XML rules .....	10
<b>2 Recommended Customer-to-PSP and PSP-to-Customer messages .....</b>	<b>11</b>
2.1 Customer to PSP Credit Transfer Information (DS-01).....	11
2.1.1 Use of the Customer Credit Transfer Initiation (pain.001.001.09) .....	11
2.2 PSP to Customer Reject, Negative or Positive response Credit Transfer Dataset (based on DS-03) .....	49
2.2.1 Recommended Use of the Customer Payment Status Report (pain.002.001.10).....	49
2.2.2 Message Element Specifications for status codes .....	61
2.2.3 Message Element Specifications for reason codes .....	62
<b>3 List of changes in the NPC Credit Transfer Customer-to-PSP Implementation Guidelines 2023 version 1.3</b>	<b>64</b>
3.1 List of changes 2023 v 1.3 relative to 2023 v 1.2 .....	64
3.2 List of changes 2023 v 1.2 relative to 2023 v 1.1 .....	64
3.3 List of changes 2023 v 1.1 relative to 2023 v 1.0 .....	65
3.4 List of changes 2023 v 1.0 relative to 2020 v 1.1 .....	66

## 0. Document Information

### 0.1 References

This section lists relevant documents of interest.

	Document Number	Title	Issued by:
[1]	NPC001-01	NPC Credit Transfer Scheme Rulebook 2023 Version 1.0	NPC
[2]	-	ISO 20022 XML Credit Transfers and Related Messages. <ul style="list-style-type: none"> <li>Initiation</li> </ul> <p>Note: The 2023 IGs are based on the 2019 message version of ISO 20022.</p>	<a href="#">ISO 20022</a>
[3]	ISO 3166	Country Codes	ISO
[4]	ISO 4217	Currency Code List	ISO
[5]	ISO 9362	Business Identifier Codes (BIC)	ISO
[6]	ISO 13616	IBAN: International Bank Account Number	ISO <sup>1</sup>
[7]	ISO 11649	Structured creditor reference to remittance information	ISO
[8]	EPC230-15	Clarification Paper on the Use of Slashes in References, Identifications, and Identifiers	EPC
[9]	NPC100-01	NPC Scheme Currencies – currencies covered by the scheme	NPC

<sup>1</sup> See also [http://www.swift.com/products/bic\\_registration/iban\\_format\\_registration](http://www.swift.com/products/bic_registration/iban_format_registration)

## 0.2 Change History

Issue number	Dated	Reason for revision
2020 v.1.0	2020-03-27	Decided by NPC Scheme Management Committee (SMC) 26 Mars 2020.
2020 v.1.0.1	2020-09-09	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 10 June 2020. All changes listed in in chapter 3.
2020 v.1.1	2021-04-30	Update agreed by NCT & NCT Inst WG and decided by Scheme Management Committee (SMC) 13 April 2021.
2023 v.1.0	2022-07-11	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 8 June 2022. All changes listed in in chapter 3.
2023 v.1.1	2022-12-06	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 24 November 2022. All changes listed in in chapter 3.
2023 v.1.2	2023-04-17	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 17 April 2023. All changes listed in in chapter 3.
2023 v.1.3	2023-11-27	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 23 November 2023. All changes listed in in chapter 3.

## 0.3 Purpose of Document

The objective of these Guidelines is to define the recommended rules to be applied to the ISO 20022 XML message standards for the implementation of the NPC Credit Transfers in the customer-to-Payment Service Provider (PSP) space.

**Note:** The term “bank” has been replaced by “PSP” in all the NPC payment scheme rulebooks and associated implementation guidelines to formally reflect the changes introduced by the Payment Services Directive (PSD) to the categories of institutions that can offer payment services, and the variety in PSP categories that are eligible to adhere to the NPC payment schemes. However, please note that in the context of ISO, the term “bank” is still used.

**Note:** The term ‘Customer’ is to be understood as ‘Payment Service User’ (PSU), meaning a natural or legal person making use of a payment service in the capacity of payer, payee, or both. Such person can take up the role of Originator and/or Beneficiary under the Scheme.

# 1. Introduction

This document sets out the NPC recommended rules for implementing the credit transfer ISO 20022 XML initiation message standards. The NPC Credit Transfer Scheme Rulebook defines data sets which are implemented in the relevant ISO 20022 XML message standard of which the following are covered:

NPC Credit Transfer Scheme Rulebook	ISO 20022 XML Message Standards
DS-01 <i>Customer-to-PSP Credit Transfer Information</i>	Customer Credit Transfer Initiation (pain.001.001.09)
DS-04 <i>PSP-to-Customer Credit Transfer Information</i>	Statements/advice ISO 20022 XML standards are covered separately.
<i>Reject, Negative or Positive response based on DS-03 for the PSP-to-Customer reject.</i>	Customer Payment Status Report (pain.002.001.10)

The Guidelines for the customer-to-PSP and PSP-to-customer XML message standards are a recommendation from the NPC on how to support the XML message standards at the request of the Originator or Beneficiary. This means that a Scheme Participant is recommended to accept the messages as described in these guidelines.

## 1.1 Coverage of the NPC customer-to-PSP Implementation Guidelines

The purpose of the NPC customer-to-PSP Implementation Guidelines, hereafter referred to as the Guidelines, is to provide guidance on the use of the payment initiation ISO 20022 XML standards (the 'pain' messages) in initiating NPC core payments as defined in the NPC scheme rulebooks and supplemented by processing requirements.

The Guidelines are fully aligned to the NPC core requirements when defined in the Rulebook and identify message elements needed for initiating NPC payments while recognizing message elements that may be available for use in Additional Optional Services (AOS), as shown below.



Figure 1

Global ISO 20022 XML Message Standards			
Message elements from the ISO messages corresponding to Rulebook requirements	Message elements that are mandatory in the ISO messages or needed for Processing	Message elements from the ISO messages available for use by AOS within an NPC Governance framework	Message elements from ISO messages not applicable to NPC
<b>NPC Implementation Guidelines for NPC Core subset, identifying elements</b> <ul style="list-style-type: none"> <li>- to be used as defined in ISO</li> <li>- to be used with NPC usage rules (from or completing the Rulebook)</li> </ul> <b>Note: yellow fields can be used in a specific way for an AOS.</b>		To be developed and documented by AOS Communities	Not available for use in NPC payments
NPC Payments			

These Guidelines define the NPC Core Mandatory Subset<sup>2</sup> of the Global ISO 20022 XML standard that consists of message elements:

- required in the Rulebook as business requirements
- needed for processing by PSPs, clearing and settlement mechanisms and PSP customers

Elements needed for specific national regulatory requirements are not considered in these guidelines. They have to be dealt with at national level without being regarded as an AOS.

These message elements define the **NPC core service** and are denoted by yellow shading in the message structures given in the following chapters. Only these elements are further detailed with relevant NPC core requirements, such as the use of the message element, its components or the values that must be used. Usage rules, for example, may indicate limits on the number of repetitions, or code value restrictions, while format rules may be used to indicate the allowable combinations of components of a message element.

These Guidelines also recognise message elements and the usage rules in the ISO 20022 XML standard that may be available for use in an AOS, subject to a governance framework to be defined by the NPC. The definition and documentation of these message elements are a matter for the AOS communities involved. These message elements are denoted by white shading.

Where there are message elements that do not apply to NPC payments, these are denoted with red shading in the right-most column of the message structures. To date, few such message elements have been identified.

## 1.2 Use of these Guidelines by the instructing and instructed parties<sup>3</sup>

- NPC core payments are executed using messages only containing message elements defined as part of the NPC Core Subset (shaded yellow in Figure 2).
- Payments that include message elements that are defined and documented by AOS communities (shaded white/yellow in Figure 2) are considered as NPC payments, but not as NPC core payments.

<sup>2</sup> The NPC Core Mandatory Subset is hereafter known as the NPC core service.

<sup>3</sup> Instructing and instructed parties include CSMs.

- It is the responsibility of the instructing customer and instructed PSP of the message to ensure that message elements defined for use in an AOS are only included in messages sent to AOS community members.
- The instructed PSP receiving a message containing AOS message elements, but which is not a member of this AOS community, may ignore the information, that is, not use it for processing, nor forward it to the next party in the chain. The instructed PSP, however, may reject the message for this reason.

### 1.3 Notation Conventions

The Guidelines are presented in a similar format than the one used in the ISO 20022 XML standard.

#	NPC Mul	Message Element	NPC Core Requirements
1.00	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2	<i>NPC Usage Rule(s)</i> (e.g., Mandatory) <i>NPC Format Rule(s)</i> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> (Yellow: Message Element that is part of the NPC Core Service)
	1..1		<b>XML Tag</b> xs:choice
1.01	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>NPC Rulebook</i> (Attribute used in Rulebook) <i>NPC Usage Rule(s)</i> (e.g., Only 'NPCA' is allowed.) <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b> (Yellow: Message Element that is part of the NPC Core Service)
			<b>NPC Code restrictions</b>
			<b>NPCA</b> <i>Nordic Payments Council Area Transfer, payments must be executed following the NPC Area Payment scheme.</i>
1.02	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> (White: Message Element that is not part of the Core Service but is available for use in an NPC AOS)
1.0n	0..1	Message root +Group Header ++Sublevel 1	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> (Red: Message Element that is not to be used in NPC Payments)

Figure 2

Where:

- Column 1 indicates the message element Index number specific to these Implementation Guidelines. As a result, the Index numbers differ from the ones used in the relating ISO 20022 Message Definition Report, PDF version.
- Components of message elements that are not allowed in NPC payments or where no NPC requirements are defined are not displayed in full as the ISO 20022 XML standard applies.

- Column 2 indicates the mandatory or optional status and the number of repetitions defined by the NPC Core Requirements, e.g.:
  - 0..1 element is optional and may only be present once
  - 0..n element is optional with unlimited repetition
  - 1..1 element is mandatory and must be present exactly once
  - 1..n element is mandatory with unlimited repetition

The displayed NPC multiplicity may thus differ from the one of the ISO 20022 XML standards. When an element is shaded yellow, possible remaining ISO 20022 occurrences are available for use in an AOS.

Empty elements are not allowed (i.e., a message shall not contain elements without content).

- Column 3 indicates the full path of an element where the last line contains the name of the message element as defined in the ISO 20022 XML standard. When an element contains sub-elements, these are indented to the right and noted with a plus sign (+) per level.
- Column 4 specifies in italic characters the NPC Core Requirements as additional rules to those specified in the ISO 20022 XML standard, which are shown in non-italic characters.
  - When defined in the Rulebook, the attribute is indicated by the attribute name and where applicable, the number, i.e., AT-nn. Those message elements are shaded yellow.
  - When the message element relates to inter-PSP processing requirements, it is shaded yellow.
  - When the message element specified in the ISO 20022 XML standard is used for NPC payments without change (regarding the definition and any usage rules), no specific NPC Core requirements are provided and is shaded yellow.
  - When the message element is specified in the ISO 20022 XML standard as optional, but is mandatory in NPC Core requirements, this is specified as 'Mandatory' and is shaded yellow.
  - When the message element is not available for use in NPC payments, this is indicated with red shading. Note that these message elements are similarly not available for use in an AOS.
  - The NPC length is indicated for every message element (if applicable), even if it is the same length as in the ISO 20022 XML standard.

Column 4 may also indicate conditional relationships between components of a message element, for example, either component 1 or component 2 must be present, but not both (indicated, in empty lines without index number, in the column 4 with XML Tag 'xs:choice'). In such case, the choice is to be made between the two following sub-elements, if both are shaded yellow.

## 1.4 Character Set

The character set issue centres on the use of the full set characters in the message elements. Two considerations are:

- While PSPs and their customers must be allowed to use the character set currently in use at national level,
- PSPs and their customers cannot be required to support the full character set used in ISO 20022 XML messages.

Therefore:

- The ISO 20022 XML messages allow for the full range of global language requirements (UTF-8).



- PSPs and their customers must be able to support the Latin character set commonly used in international communication and in addition to this the Scandinavian characters and the @-sign, as follows:

a b c d e f g h i j k l m n o p q r s t u v w x y z å ä ö æ ø  
 A B C D E F G H I J K L M N O P Q R S T U V W X Y Z Å Ä Ö Æ Ø  
 0 1 2 3 4 5 6 7 8 9  
 / - ? : ( ) . , ' + @  
 Space

- References, identifications, and identifiers must respect the following [8]:
  - Content is restricted to the Latin character set as defined above
  - Content must not start or end with a '/'
  - Content must not contain '//'

Note: When a slash is used as delimiter between the attribute number (AT-XX) or code (ABCD) and the data content, no space is allowed directly after this slash.

However, there may be bilateral or multilateral agreements to support one or more sets of characters beyond the Latin character set including the Scandinavian characters and the @-sign referred to above.

## 1.5 General Message Element Specifications

### 1.5.1 BIC

The BIC used to identify financial institutions (Agents in the ISO 20022 XML standards) may be either BIC 11 or BIC 8.

### 1.5.2 Currency

Unlike the EPC SEPA Credit Transfer Rulebook, the NPC Credit Transfer Rulebook allows more than one currency. Currencies covered by the scheme are called 'Scheme Currencies' and are listed in the reference document *Scheme Currencies* [9].

### 1.5.3 Alias and Proxy

In the Nordic payment market it is common that an 'Alias' or 'Proxy' is used to identify an Originator's and/or a Beneficiary's account. Therefore, ISO 20022 elements in the Debtor Account and Creditor Account sections are utilized in order to enable (Originators) to initiate their payment from – and to – an 'Alias' or 'Proxy' instead of an IBAN, and for Beneficiaries to still be able to collect payments through an 'Alias' or 'Proxy' instead of their IBAN. NPC usage is described in the NPC Credit Transfer Scheme Inter-PSP Implementation Guideline in the Debtor Account and Creditor Account sections. For ease of use, National Account Number will be treated as an Alias, too. Attribute AT-11 Originator Proxy/Alias and AT-25 Beneficiary Proxy/Alias should be used.

### 1.5.4 Structured creditor references, e.g. OCR-references

In the Nordic payment market, there is a legacy in some countries to use existing national rules for creditor reference (i.e. OCR-references or Norwegian KID). These references are only used in combination with a corresponding 'Alias' or the National Account Number itself. The different national creditor rules have solutions for maintaining and performing necessary distribution of validation rules for the creditor reference. Therefore, when Originators have entered an OCR-reference or KID it is mandatory that the Originator PSP validates the 'structured creditor reference' by checking the rules for validation connected to the respective 'Alias' or National Account Number, to ensure the correctness of the OCR-reference or KID.

### 1.5.5 Extended remittance information, up to 999 occurrences of structured references

In the Nordic payment market it is a market practice to be able to enter remittance data with more than one occurrence of structured reference. Therefore, when using Extended Remittance Information, the Originator can refer to up to 999 invoices and credit notes in structured format to each Credit Transfer payment. It is recommended that all references have a referred document amount and it is recommended that the Originator PSP (Debtor PSP) ensures that the amount of the Credit Transfer equals the sum of the amounts of the referred references.

In comparison with EPC IGs, the NPC IGs do not use a specific attribute (AT-61 and AT-62 in EPC IGs) for the Extended remittance information. Instead the same attribute – AT-05 – is used for both payments with Extended Remittance Information and payments without.

The ERI-option supports the transmission and the processing of the following combination of RI in Credit Transfer Instructions and Transactions:

- One occurrence of 140 characters of unstructured RI and
- Up to 999 occurrences of 280 characters of structured RI based on the ISO 20022 standard or OCR-references described as above. The Originator can refer to up to 999 invoices and credit notes in structured format to each Credit Transfer payment. All references must also have a referred amount and be of the same currency.

When using more than one occurrence of the structured remittance information extended remittance information, ERI) both the structured and the unstructured reference must be used. In case of returns, rejects or similar R-messages only the unstructured remittance information sent by the Originator to the Beneficiary in the NPC Credit Transfer Instruction needs to be forwarded.

## 1.6 Implementation of ISO 20022 XML rules

This document should be read in conjunction with the ISO 20022 XML message standards.

## 2 Recommended Customer-to-PSP and PSP-to-Customer messages

### 2.1 Customer to PSP Credit Transfer Information (DS-01)

#### 2.1.1 Use of the Customer Credit Transfer Initiation (pain.001.001.09)

The message is used to transport the customer-to-PSP Credit Transfer Information sent by the Originator to the Originator PSP.

The message caters for bulk and single payment instructions.

**Note:** In case the transaction is a transfer back related to an earlier executed NPC Credit Transfer (NCT) Transaction (as per 'Remarks' under DS-01 in the NCT rulebook), the 'purpose' element must be populated with 'RRCT' (Reimbursement Received Credit Transfer) or another code meaningful for identifying the NCT as a transfer back.

**Note:** In case the transaction is the result of a received Request-to-Pay (RTP) message, the 'Purpose' element must be populated with 'RRTP' (Related to a Request-to-Pay (RTP)). Further details on RTP are to be found in the SRTP documentation.

**Note:** In case AT-11 The Proxy/Alias of the account of the Originator or AT-25 The Proxy/Alias of the account of the Beneficiary is used, there are two options for how to state Proxy/Alias:

1. To state the Proxy/Alias under SchemeName as a Code or Proprietary Code. This is the only valid option for National Account Number/BBAN.
2. To state the Proxy/Alias under Proxy element as a Proprietary Code.

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
		Document	<b>XML Tag Type</b>	Document Document
	1..1	Customer Credit Transfer Initiation V09	<b>ISO Name ISO Definition</b>	Customer Credit Transfer Initiation V09 Scope The CustomerCreditTransferInitiation message is sent by the initiating party to the forwarding agent or debtor agent. It is used to request movement of funds from the debtor account to a creditor. <b>XML Tag Type</b> CstmrCdtTrfInitn CustomerCreditTransferInitiationV09
1.0	1..1	Customer Credit Transfer Initiation V09 +Group Header	<b>ISO Name ISO Definition</b>	Group Header Set of characteristics shared by all individual transactions included in the message. <b>XML Tag Type</b> GrpHdr GroupHeader85
1.1	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Message Identification	<b>ISO Name ISO Definition</b>	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. <b>XML Tag Type</b> MsgId Max35Text <b>ISO Length</b> 1 .. 35 <b>NPC Length</b> 1 .. 35
1.2	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Creation Date Time	<b>ISO Name ISO Definition XML Tag Type</b>	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..2	Customer Credit Transfer Initiation V09 +Group Header ++Authorisation	<b>ISO Name ISO Definition</b>	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message.  Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. <b>XML Tag Type</b> Authstn Authorisation1Choice
1.4	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Number Of Transactions	<b>NPC Usage Rule(s)</b> <b>ISO Name ISO Definition</b> <b>XML Tag Type Pattern</b>	<i>The validation of this data element depends on pre-agreed customer-to-PSP conditions.</i> Number Of Transactions Number of individual transactions contained in the message. NbOfTx Max15NumericText [0-9]{1,15}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
1.5	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Control Sum	<b>NPC Usage Rule(s)</b> <i>The validation of this data element depends on pre-agreed customer-to-PSP conditions.</i> <b>NPC Format Rule(s)</b> <i>The fractional part has a maximum of two digits.</i> <b>ISO Name</b> Control Sum <b>ISO Definition</b> Total of all individual amounts included in the message, irrespective of currencies. <b>XML Tag</b> CtrlSum <b>Type</b> DecimalNumber <b>NPC FractDigits</b> 2 <b>TotalDigits</b> 18	
1.6	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party	<b>ISO Name</b> Initiating Party <b>ISO Definition</b> Party that initiates the payment.  Usage: This can either be the debtor or the party that initiates the credit transfer on behalf of the debtor. <b>XML Tag</b> InitgPty <b>Type</b> PartyIdentification135	
1.7	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Name	<b>NPC Format Rule(s)</b> <i>'Name' is limited to 70 characters in length.</i> <b>ISO Name</b> Name <b>ISO Definition</b> Name by which a party is known and which is usually used to identify that party. <b>XML Tag</b> Nm <b>Type</b> Max140Text <b>ISO Length</b> 1 .. 140 <b>NPC Length</b> 1 .. 70	
1.8	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Postal Address	<b>ISO Name</b> Postal Address <b>ISO Definition</b> Information that locates and identifies a specific address, as defined by postal services. <b>XML Tag</b> PstlAdr <b>Type</b> PostalAddress24	
1.9	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Identification	<b>ISO Name</b> Identification <b>ISO Definition</b> Unique and unambiguous identification of a party. <b>XML Tag</b> Id <b>Type</b> Party38Choice	
	1..1		<b>XML Tag</b> xs:choice	
1.10	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Identification ++++Organisation Identification	<b>NPC Usage Rule(s)</b> <i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> <b>ISO Name</b> Organisation Identification <b>ISO Definition</b> Unique and unambiguous way to identify an organisation. <b>XML Tag</b> OrgId <b>Type</b> OrganisationIdentification29	
1.11	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Identification ++++Private Identification	<b>NPC Usage Rule(s)</b> <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> <b>ISO Name</b> Private Identification <b>ISO Definition</b> Unique and unambiguous identification of a person, for example a passport. <b>XML Tag</b> PrvtId <b>Type</b> PersonIdentification13	
1.12	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Country Of Residence	<b>ISO Name</b> Country Of Residence <b>ISO Definition</b> Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. <b>XML Tag</b> CtryOfRes <b>Type</b> CountryCode <b>Pattern</b> [A-Z]{2,2}	
1.13	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Contact Details	<b>ISO Name</b> Contact Details <b>ISO Definition</b> Set of elements used to indicate how to contact the party. <b>XML Tag</b> CtctDtls <b>Type</b> Contact4	



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
1.14	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Forwarding Agent	ISO Name ISO Definition  XML Tag Type	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution. FwdgAgt BranchAndFinancialInstitutionIdentification6
2.0	1..n	Customer Credit Transfer Initiation V09 +Payment Information	ISO Name ISO Definition  XML Tag Type	Payment Information Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation. PmtInf PaymentInstruction30
2.1	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Information Identification	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Payment Information Identification Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message. PmtInfId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Method	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	'TRF' is to be used for Credit Transfer; CHK to be used for Cheque. Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod3Code
			NPC Code Restrictions	
			CHK	Cheque Written order to a bank to pay a certain amount of money from one person to another person.
			TRF	CreditTransfer Transfer of an amount of money in the books of the account servicer.
2.3	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Batch Booking	NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type	If present and contains 'true', batch booking is requested. If present and contains 'false', booking per transaction is requested. If element is not present, pre-agreed customer-to-PSP conditions apply. Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
2.4	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Number Of Transactions	NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type Pattern	The validation of this data element depends on pre-agreed customer-to-PSP conditions. Number Of Transactions Number of individual transactions contained in the payment information group. NbOfTx Max15NumericText [0-9]{1,15}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.5	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Control Sum	<b>NPC Usage Rule(s)</b> <i>The validation of this data element depends on pre-agreed customer-to-PSP conditions.</i> <b>NPC Format Rule(s)</b> <i>The fractional part has a maximum of two digits.</i> <b>ISO Name</b> Control Sum <b>ISO Definition</b> Total of all individual amounts included in the group, irrespective of currencies. <b>XML Tag</b> CtrlSum <b>Type</b> DecimalNumber <b>NPC FractDigits</b> 2 <b>TotalDigits</b> 18	
2.6	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information	<b>NPC Usage Rule(s)</b> <i>'Payment Type Information' must be present either here or under 'Credit Transfer Transaction Information'.</i> <b>ISO Name</b> Payment Type Information <b>ISO Definition</b> Set of elements used to further specify the type of transaction. <b>XML Tag</b> PmtTpInf <b>Type</b> PaymentTypeInformation26	
2.7	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Instruction Priority	<b>NPC Usage Rule(s)</b> <i>If present, pre-agreed customer-to-PSP conditions apply. Based on whether priority processing vs. normal processing is offered by the PSP.</i> <b>ISO Name</b> Instruction Priority <b>ISO Definition</b> Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. <b>XML Tag</b> InstrPrty <b>Type</b> Priority2Code	
2.8	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Service Level	<b>NPC Usage Rule(s)</b> <i>Usage is recommended. Only one occurrence is allowed.</i> <b>ISO Name</b> Service Level <b>ISO Definition</b> Agreement under which or rules under which the transaction should be processed. <b>XML Tag</b> SvcLvl <b>Type</b> ServiceLevel8Choice	
	1..1		<b>XML Tag</b> xs:choice	
2.9	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Service Level ++++Code	<b>NPC Rulebook</b> <i>AT-40 The identification code of the Scheme.</i> <b>NPC Usage Rule(s)</b> <i>Only 'NPCA' is allowed.</i> <b>ISO Name</b> Code <b>ISO Definition</b> Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. <b>XML Tag</b> Cd <b>Type</b> ExternalServiceLevel1Code <b>ISO Length</b> 1 .. 4 <b>NPC Length</b> 1 .. 4	
			NPC Code Restrictions	
			<b>NPCA</b> <i>NordicPaymentsCouncilAreaTransfer Payments must be executed following the NPC Area Payment scheme.</i>	
2.10	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Service Level ++++Proprietary	<b>ISO Name</b> Proprietary <b>ISO Definition</b> Specifies a pre-agreed service or level of service between the parties, as a proprietary code. <b>XML Tag</b> Prtry <b>Type</b> Max35Text <b>ISO Length</b> 1 .. 35 <b>NPC Length</b> 1 .. 35	

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.11	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Local Instrument	ISO Name ISO Definition  XML Tag Type	Local Instrument User community specific instrument.  Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level. LclInstrm LocalInstrument2Choice
	1..1		XML Tag	xs:choice
2.12	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Local Instrument ++++Code	NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Recommended to use 'PERI' for Payments with Extended Remittance Information. Code Specifies the local instrument, as published in an external local instrument code list. Cd ExternalLocalInstrument1Code 1 .. 35 1 .. 35
2.13	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Local Instrument ++++Proprietary	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Proprietary Specifies the local instrument, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35
2.14	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Category Purpose	NPC Rulebook NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type	AT-45 The category purpose of the NPC Credit Transfer. If provided by the Originator the Originator PSP, must forward the 'Category Purpose' to the Beneficiary PSP. Category Purpose Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain. CtgyPurp CategoryPurpose1Choice
	1..1		XML Tag	xs:choice
2.15	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Category Purpose ++++Code	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Code Category purpose, as published in an external category purpose code list. Cd ExternalCategoryPurpose1Code 1 .. 4 1 .. 4
2.16	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Category Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Category purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.17	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Requested Execution Date	<i>NPC Rulebook</i> <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<i>AT-07 The Requested Execution Date of the Credit Transfer Instruction.</i> Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
	1..1		<b>XML Tag</b>	xs:choice
2.18	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Requested Execution Date +++Date	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Date Specified date. Dt ISODate
2.19	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Requested Execution Date +++Date Time	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Date Time Specified date and time. DtTm ISODateTime
2.20	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Pooling Adjustment Date	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Pooling Adjustment Date Date used for the correction of the value date of a cash pool movement that has been posted with a different value date. PoolgAdjstmntDt ISODate
2.21	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification135
2.22	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Name	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> <i>NPC Format Rule(s)</i> <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	<i>AT-02 The name of the Originator.</i> <i>Mandatory.</i> <i>'Name' is limited to 70 characters in length.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.23	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<i>AT-03 The address of the Originator.</i> <i>If a Postal Address sub-element other than 'Address Line' and 'Country' is used, then 'Address Line' is forbidden. A combination of Address Line and Country is allowed. If 'Address Line' is not used, then at least Town Name and Country must be used.</i> <i>Address line is not to be used after 2025. Only structured postal address elements must be used.</i> Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.24	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Address Type	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.25	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.26	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.27	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.28	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.29	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.30	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.31	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.32	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70
2.33	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.34	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.35	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.36	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	District Name Identifies a subdivision within a country sub-division. DstrctNm Max35Text 1 .. 35 1 .. 35
2.37	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.38	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.39	0..2	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Address Line	NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Only two occurrences are allowed. If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed. Address line is not to be used after 2025. Only structured postal address elements must be used. Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.40	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification	NPC Rulebook ISO Name ISO Definition  XML Tag Type	AT-10 The Originator identification code. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.41	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification	NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type	Either 'AnyBIC', 'LEI' or 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.42	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Any BIC	ISO Name ISO Definition XML Tag Type Pattern	Any BIC Business identification code of the organisation. AnyBIC AnyBICDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}
2.43	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identification as an alternate identification for a party. LEI LEIIdentifier [A-Z0-9]{18,18}[0-9]{2,2}
2.44	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an organisation, as assigned by an institution, using an identification scheme. Othr GenericOrganisationIdentification1
2.45	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other ++++++Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Identification Identification assigned by an institution. Id Max35Text 1 .. 35 1 .. 35
2.46	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm OrganisationIdentificationSchemeName1Choice
	1..1		XML Tag	xs:choice
2.47	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other ++++++Scheme Name +++++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalOrganisationIdentification1Code 1 .. 4 1 .. 4
2.48	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other ++++++Scheme Name +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.49	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.50	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or 'Other' is allowed Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.51	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth	ISO Name ISO Definition XML Tag Type	Date And Place Of Birth Date and place of birth of a person. DtAndPlcOfBirth DateAndPlaceOfBirth1
2.52	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++Birth Date	ISO Name ISO Definition XML Tag Type	Birth Date Date on which a person is born. BirthDt ISODate
2.53	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++Province Of Birth	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Province Of Birth Province where a person was born. PrvcOfBirth Max35Text 1 .. 35 1 .. 35
2.54	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++City Of Birth	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	City Of Birth City where a person was born. CityOfBirth Max35Text 1 .. 35 1 .. 35
2.55	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++Country Of Birth	ISO Name ISO Definition XML Tag Type Pattern	Country Of Birth Country where a person was born. CtryOfBirth CountryCode [A-Z]{2,2}
2.56	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of a person, as assigned by an institution, using an identification scheme. Othr GenericPersonIdentification1
2.57	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
2.58	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm PersonIdentificationSchemeName1Choice
	1..1		XML Tag	xs:choice
2.59	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Scheme Name +++++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalPersonIdentification1Code 1 .. 4 1 .. 4

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.60	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Scheme Name +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.61	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.62	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.63	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.64	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-01 The IBAN of the account of the Originator. AT-11 The Proxy/Alias of the account of the Originator. Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
2.65	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory, either 'IBAN' or 'Other' should be populated. 'Other' could be 'Alias', 'Proxy' or 'National Account Number'. Important: Either Identification/SchemeName or Identification/Proxy to be used. Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice
	1..1		XML Tag	xs:choice
2.66	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++IBAN	NPC Rulebook ISO Name ISO Definition XML Tag Type Pattern	AT-01 The IBAN of the account of the Originator. IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.67	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i>	<i>AT-11 The Proxy/Alias of the account of the Originator.</i> <i>When 'Proxy', 'Alias' or 'BBAN' is populated using 'Other', 'SchemeName' must be specified together with code (BBAN) or Proprietary code e.g. SE BGNR. 'Other' needs to be included if proxy element (2.76) is used.</i>  Other Unique identification of an account, as assigned by the account servicer, using an identification scheme.  Othr GenericAccountIdentification1
2.68	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Identification	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	<i>If 'Proxy' or 'Alias' is provided in the Proxy element state NOTPROVIDED.</i>  Identification Identification assigned by an institution.  Id Max34Text 1 .. 34 1 .. 34
2.69	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Scheme Name	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	<i>Proxy', 'Alias' or 'National Account number' schemes defined by Proprietary code (e.g. Swedish Bankgiro number, Swedish Plusgiro number etc) or code (e.g. National Account Number).</i> <i>Mandatory if National Account Number (BBAN).</i>  Scheme Name Name of the identification scheme.  SchmeNm AccountSchemeName1Choice
	1..1		<i>XML Tag</i>	xs:choice
2.70	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Scheme Name +++++Code	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	<i>Code used for National Account Number (BBAN).</i>  Code Name of the identification scheme, in a coded form as published in an external list.  Cd ExternalAccountIdentification1Code 1 .. 4 1 .. 4
2.71	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Scheme Name +++++Proprietary	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	<i>Proprietary code are used to define Scheme Name.</i>  Proprietary Name of the identification scheme, in a free text form.  Prtry Max35Text 1 .. 35 1 .. 35
2.72	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Issuer	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	Issuer Entity that assigns the identification.  Issr Max35Text 1 .. 35 1 .. 35
2.73	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Type	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Type Specifies the nature, or use of the account.  Tp CashAccountType2Choice



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.74	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Currency	ISO Name ISO Definition      XML Tag Type Pattern	Currency Identification of the currency in which the account is held.  Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.75	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Name	ISO Name ISO Definition      XML Tag Type ISO Length NPC Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.  Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.76	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy	ISO Name ISO Definition  XML Tag Type	Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.77	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Type	ISO Name ISO Definition XML Tag Type	Type Type of the proxy identification. Tp ProxyAccountType1Choice
	1..1		XML Tag	xs:choice
2.78	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Type +++++Code	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalProxyAccountType1Code 1 .. 4 1 .. 4
2.79	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Type +++++Proprietary	NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Proprietary used to define the Proxy (e.g. Swedish Bankgiro number, Swedish Plusgiro number etc). Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.80	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Identification	<i>NPC Usage Rule(s)</i>	'Alias'/'Proxy' defined by Code or Proprietary code (Swedish Bankgiro number, Swedish Plusgiro number etc). Identification Identification used to indicate the account identification under another specified name. Id Max2048Text 1 .. 2048 1 .. 2048
2.81	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
2.82	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification	<i>NPC Usage Rule(s)</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Either BICFI or 'Other/Identification' must be used. BICFI is recommended. Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstnId FinancialInstitutionIdentification18
2.83	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++BICFI	<i>NPC Rulebook</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>Pattern</i>	AT-06 The BIC code of the Originator PSP. BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}
2.84	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Clearing System Member Identification	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbId ClearingSystemMemberIdentification2
2.85	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++LEI	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>Pattern</i>	LEI Legal entity identifier of the financial institution. LEI LEIIdentifier [A-Z0-9]{18,18}[0-9]{2,2}
2.86	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Name	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
2.87	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Postal Address	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.88	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.89	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other +++++Identification	<i>NPC Usage Rule(s)</i> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Only 'NOTPROVIDED' is allowed. Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
2.90	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other +++++Scheme Name	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
2.91	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other +++++Issuer	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.92	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Branch Identification	<b>ISO Name</b> <b>ISO Definition</b>     <b>XML Tag</b> <b>Type</b>	Branch Identification Identifies a specific branch of a financial institution.  Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
2.93	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent Account	<b>ISO Name</b> <b>ISO Definition</b>   <b>XML Tag</b> <b>Type</b>	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
2.94	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Instruction For Debtor Agent	<b>ISO Name</b> <b>ISO Definition</b>     <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Instruction For Debtor Agent Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent.  Usage: when present, then the instructions for the debtor agent apply for all credit transfer transaction information occurrences, present in the payment information. InstrForDbtrAgt Max140Text 1 .. 140 1 .. 140
2.95	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor	<b>ISO Name</b> <b>ISO Definition</b>   <b>XML Tag</b> <b>Type</b>	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification135

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.96	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Name	<b>NPC Rulebook</b> AT-08 The name of the Originator Reference Party. <b>NPC Usage Rule(s)</b> If Ultimate Debtor is used, name is mandatory. <b>NPC Format Rule(s)</b> 'Name' is limited to 70 characters in length. <b>ISO Name</b> Name <b>ISO Definition</b> Name by which a party is known and which is usually used to identify that party. <b>XML Tag</b> Nm <b>Type</b> Max140Text <b>ISO Length</b> 1 .. 140 <b>NPC Length</b> 1 .. 70	
2.97	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Postal Address	<b>NPC Usage Rule(s)</b> If a Postal Address sub-element other than 'Address Line' and 'Country' is used, then 'Address Line' is forbidden. A combination of 'Address Line' and 'Country' is allowed. If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used. 'Address Line' is not to be used after 2025. Only structured postal address elements must be used. <b>ISO Name</b> Postal Address <b>ISO Definition</b> Information that locates and identifies a specific address, as defined by postal services. <b>XML Tag</b> PstlAdr <b>Type</b> PostalAddress24	
2.98	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Identification	<b>NPC Rulebook</b> AT-09 The identification code of the Originator Reference Party <b>ISO Name</b> Identification <b>ISO Definition</b> Unique and unambiguous identification of a party. <b>XML Tag</b> Id <b>Type</b> Party38Choice	
	1..1		<b>XML Tag</b> xs:choice	
2.99	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Identification ++++Organisation Identification	<b>NPC Usage Rule(s)</b> Either 'AnyBIC', 'LEI' or 'Other' is allowed. <b>ISO Name</b> Organisation Identification <b>ISO Definition</b> Unique and unambiguous way to identify an organisation. <b>XML Tag</b> OrgId <b>Type</b> OrganisationIdentification29	
2.100	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Identification ++++Private Identification	<b>NPC Usage Rule(s)</b> Either 'Date and Place of Birth' or 'Other' is allowed. <b>ISO Name</b> Private Identification <b>ISO Definition</b> Unique and unambiguous identification of a person, for example a passport. <b>XML Tag</b> PrvtId <b>Type</b> PersonIdentification13	
2.101	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Country Of Residence	<b>ISO Name</b> Country Of Residence <b>ISO Definition</b> Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. <b>XML Tag</b> CtryOfRes <b>Type</b> CountryCode <b>Pattern</b> [A-Z]{2,2}	
2.102	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Contact Details	<b>ISO Name</b> Contact Details <b>ISO Definition</b> Set of elements used to indicate how to contact the party. <b>XML Tag</b> CtctDtls <b>Type</b> Contact4	

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.103	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Charge Bearer	<p><b>NPC Usage Rule(s)</b> 'SHAR' or 'SLEV' to be used. It is recommended that this element is specified at 'Payment Information' level.</p> <p><b>ISO Name</b> Charge Bearer</p> <p><b>ISO Definition</b> Specifies which party/parties will bear the charges associated with the processing of the payment transaction.</p> <p><b>XML Tag</b> ChrgBr</p> <p><b>Type</b> ChargeBearerType1Code</p>	
			<b>NPC Code Restrictions</b>	
			<b>SHAR</b>	Shared Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor.
			<b>SLEV</b>	FollowingServiceLevel for NPC Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In addition, the full amount need to be credited to Beneficiary.
2.104	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Charges Account	<p><b>ISO Name</b> Charges Account</p> <p><b>ISO Definition</b> Account used to process charges associated with a transaction.</p> <p>Usage: Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account.</p> <p><b>XML Tag</b> ChrgsAcct</p> <p><b>Type</b> CashAccount38</p>	
2.105	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Charges Account Agent	<p><b>ISO Name</b> Charges Account Agent</p> <p><b>ISO Definition</b> Agent that services a charges account.</p> <p>Usage: Charges account agent should only be used when the charges account agent is different from the debtor agent.</p> <p><b>XML Tag</b> ChrgsAcctAgt</p> <p><b>Type</b> BranchAndFinancialInstitutionIdentification6</p>	
2.106	1..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information	<p><b>ISO Name</b> Credit Transfer Transaction Information</p> <p><b>ISO Definition</b> Provides information on the individual transaction(s) included in the message.</p> <p><b>XML Tag</b> CdtTrfTxInf</p> <p><b>Type</b> CreditTransferTransaction34</p>	
2.107	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification	<p><b>ISO Name</b> Payment Identification</p> <p><b>ISO Definition</b> Set of elements used to reference a payment instruction.</p> <p><b>XML Tag</b> PmtId</p> <p><b>Type</b> PaymentIdentification6</p>	
2.108	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification ++++Instruction Identification	<p><b>ISO Name</b> Instruction Identification</p> <p><b>ISO Definition</b> Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.</p> <p>Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.</p> <p><b>XML Tag</b> InstrId</p> <p><b>Type</b> Max35Text</p> <p><b>ISO Length</b> 1 .. 35</p> <p><b>NPC Length</b> 1 .. 35</p>	



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.109	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification ++++End To End Identification	<b>NPC Rulebook</b>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	<b>AT-41 The Originator's reference of the Credit Transfer Transaction.</b> <b>End To End Identification</b> Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.  Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. <b>EndToEndId</b> <b>Max35Text</b> 1 .. 35 1 .. 35
2.110	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification ++++UETR	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>Pattern</b>	<b>UETR</b> Universally unique identifier to provide an end-to-end reference of a payment transaction. <b>UETR</b> <b>UUIDv4Identifier</b> [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
2.111	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information	<b>NPC Usage Rule(s)</b>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<b>'Payment Type Information' must be present either here or directly under 'Payment Information'.</b> <b>Payment Type Information</b> Set of elements used to further specify the type of transaction. <b>PmtTpInf</b> <b>PaymentTypeInformation26</b>
2.112	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Instruction Priority	<b>NPC Usage Rule(s)</b>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<b>If present, pre-agreed customer-to-PSP conditions apply. Based on whether priority processing vs. normal processing is offered by the PSP.</b> <b>Instruction Priority</b> Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. <b>InstrPrty</b> <b>Priority2Code</b>
2.113	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Service Level	<b>NPC Usage Rule(s)</b>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<b>Usage is recommended. Only one occurrence is allowed .</b> <b>Service Level</b> Agreement under which or rules under which the transaction should be processed. <b>SvcLvl</b> <b>ServiceLevel8Choice</b>
	1..1		<b>XML Tag</b>	<b>xs:choice</b>
2.114	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Service Level +++++Code	<b>NPC Rulebook</b> <b>NPC Usage Rule(s)</b> <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	<b>AT-40 The identification code of the Scheme.</b> <b>Only 'NPCA' is allowed.</b> <b>Code</b> Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. <b>Cd</b> <b>ExternalServiceLevel1Code</b> 1 .. 4 1 .. 4
			<b>NPC Code Restrictions</b>	
			<b>NPCA</b>	<b>NordicPaymentsCouncilAreaTransfer Payments must be executed following the NPC Area Payment scheme.</b>

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.115	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Service Level +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Specifies a pre-agreed service or level of service between the parties, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35
2.116	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Local Instrument	ISO Name ISO Definition XML Tag Type	Local Instrument User community specific instrument.  Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level. LclInstrm LocalInstrument2Choice
	1..1		XML Tag	xs:choice
2.117	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Local Instrument +++++Code	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Recommended to use 'PERI' for Payments with Extended Remittance Information. Code Specifies the local instrument, as published in an external local instrument code list. Cd ExternalLocalInstrument1Code 1 .. 35 1 .. 35
2.118	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Local Instrument +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Specifies the local instrument, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35
2.119	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Category Purpose	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-45 The category purpose of the NPC Credit Transfer. If provided by the Originator the Originator PSP, must forward the 'Category Purpose' to the Beneficiary PSP. Category Purpose Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain. CtgyPurp CategoryPurpose1Choice
	1..1		XML Tag	xs:choice
2.120	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Category Purpose +++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Category purpose, as published in an external category purpose code list. Cd ExternalCategoryPurpose1Code 1 .. 4 1 .. 4
2.121	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Category Purpose +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Category purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.122	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Amount	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
	1..1		<b>XML Tag</b>	xs:choice
2.123	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Amount ++++Instructed Amount	<b>NPC Rulebook</b>  <b>NPC Usage Rule(s)</b> <b>NPC Format Rule(s)</b>  <b>ISO Name</b> <b>ISO Definition</b>    <b>XML Tag</b> <b>Type</b> <b>NPC FractDigits</b> <b>TotalDigits</b> <b>NPC Inclusive</b>	AT-04 The amount of the NPC Credit Transfer in the relevant Scheme Currencies and the relevant currency code. Only 'Scheme Currencies' is allowed. Amount must be 0.01 or more and 9999999999.99 or less. The fractional part has a maximum of two digits. Instructed Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.  Usage: This amount has to be transported unchanged through the transaction chain. InstdAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
2.124	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Amount ++++Equivalent Amount	<b>ISO Name</b> <b>ISO Definition</b>    <b>XML Tag</b> <b>Type</b>	Equivalent Amount Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.  EqvtAmt EquivalentAmount2
2.125	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Exchange Rate Information	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Exchange Rate Information Provides details on the currency exchange rate and contract. XchgRateInf ExchangeRate1
2.126	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Charge Bearer	<b>NPC Usage Rule(s)</b>  <b>ISO Name</b> <b>ISO Definition</b>    <b>XML Tag</b> <b>Type</b>	'SHAR' or 'SLEV' to be used. It is recommended that this element is specified at 'Payment Information' level. Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code
			<b>NPC Code Restrictions</b>	
			<b>SHAR</b>	Shared Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor.
			<b>SLEV</b>	FollowingServiceLevel for NPC Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In addition, the full amount need to be credited to Beneficiary.

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.127	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Cheque Instruction	ISO Name ISO Definition XML Tag Type	Cheque Instruction Set of elements needed to issue a cheque. ChqInstr Cheque11
2.128	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Can be present on both payment and transaction level, if present transaction level will take precedence. Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification135
2.129	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Name	NPC Rulebook NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-08 The name of the Originator Reference Party. If Ultimate Debtor is used, name is mandatory. 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.130	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Postal Address	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	If a Postal Address sub-element other than 'Address Line' and 'Country' is used, then 'Address Line' is forbidden. A combination of 'Address Line' and 'Country' is allowed. If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used. 'Address Line' is not to be used after 2025. Only structured postal address elements must be used. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.131	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-09 The identification code of the Originator Reference Party. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.132	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Identification +++++Organisation Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' or 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.133	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Identification +++++Private Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.134	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Country Of Residence	ISO Name ISO Definition  XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.135	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Contact Details	ISO Name ISO Definition  XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.136	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 1	ISO Name ISO Definition  XML Tag Type	Intermediary Agent 1 Agent between the debtor's agent and the creditor's agent.  Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2. IntrmyAgt1 BranchAndFinancialInstitutionIdentification6
2.137	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 1Account	ISO Name ISO Definition  XML Tag Type	Intermediary Agent 1Account Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain. IntrmyAgt1Acct CashAccount38
2.138	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 2	ISO Name ISO Definition  XML Tag Type	Intermediary Agent 2 Agent between the debtor's agent and the creditor's agent.  Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3. IntrmyAgt2 BranchAndFinancialInstitutionIdentification6
2.139	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 2Account	ISO Name ISO Definition  XML Tag Type	Intermediary Agent 2Account Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain. IntrmyAgt2Acct CashAccount38
2.140	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 3	ISO Name ISO Definition  XML Tag Type	Intermediary Agent 3 Agent between the debtor's agent and the creditor's agent.  Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent. IntrmyAgt3 BranchAndFinancialInstitutionIdentification6
2.141	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 3Account	ISO Name ISO Definition  XML Tag Type	Intermediary Agent 3Account Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain. IntrmyAgt3Acct CashAccount38



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.142	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent	<i>NPC Usage Rule(s)</i>	Either BIC or Clearing system member identification to be used. Clearing system member identification is only allowed in combination with National Account Number or Alias/Proxy. If the BIC is not indicated 'Creditor Agent' structure is not to be used. Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
2.143	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification	<i>NPC Usage Rule(s)</i>	Either 'BICFI' or 'Clearing system member Identification' must be used. Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstmId FinancialInstitutionIdentification18
2.144	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++BICFI	<i>NPC Rulebook</i> ISO Name ISO Definition	AT-23 The BIC code of the Beneficiary PSP. BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}
2.145	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	Clearing system member identification is only allowed in combination with National Account Number or Alias/Proxy. Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbId ClearingSystemMemberIdentification2
2.146	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification +++++Clearing System Identification	ISO Name ISO Definition XML Tag Type	Clearing System Identification Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. ClrSysId ClearingSystemIdentification2Choice
	1..1		XML Tag	xs:choice
2.147	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification +++++Clearing System Identification +++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Identification of a clearing system, in a coded form as published in an external list. Cd ExternalClearingSystemIdentification1Code 1 .. 5 1 .. 5



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.148	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification ++++++Clearing System Identification ++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Identification code for a clearing system, that has not yet been identified in the list of clearing systems. Prtry Max35Text 1 .. 35 1 .. 35
2.149	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification ++++++Member Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Member Identification Identification of a member of a clearing system. Mmbld Max35Text 1 .. 35 1 .. 35
2.150	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
2.151	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Creditor Party to which an amount of money is due. Cdtr PartyIdentification135
2.152	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Name	NPC Rulebook NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-21 The name of the Beneficiary. Mandatory. 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.153	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-22 The address of the Beneficiary. If a Postal Address sub-element other than 'Address Line' and 'Country' is used, then 'Address Line' is forbidden. A combination of 'Address Line' and 'Country' is allowed. If 'AddressLine' is not used, then at least Town Name and Country must be used. Address line is not to be used after 2025. Only structured postal address elements must be used. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.154	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.155	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.156	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.157	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.158	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.159	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.160	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Floor	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.161	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.162	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Room	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70
2.163	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.164	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.165	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.166	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++District Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	District Name Identifies a subdivision within a country sub-division. DstrctNm Max35Text 1 .. 35 1 .. 35
2.167	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.168	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.169	0..2	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Address Line	NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Only two occurrences are allowed. If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed. Address line is not to be used after 2025. Only structured postal address elements must be used. Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.170	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Identification	NPC Rulebook ISO Name ISO Definition  XML Tag Type	AT-24 The Beneficiary identification code. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.171	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Identification +++++Organisation Identification	NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type	Either 'AnyBIC', 'LEI' or 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.172	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Identification +++++Private Identification	<i>NPC Usage Rule(s)</i>	Either 'Date and Place of Birth' or 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.173	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Country Of Residence	<i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i> <i>Pattern</i>	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.174	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Contact Details	<i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i>	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.175	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account	<i>NPC Rulebook</i>  <i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i>	AT-20 The IBAN of the account of the Beneficiary. AT-25 The Proxy/Alias of the account of the Beneficiary. Creditor Account is mandatory except for cheques and cash payments (e.g. 'giro utbetaling' in Norway). Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
2.176	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification	<i>NPC Usage Rule(s)</i>   <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i>	Mandatory, either 'IBAN' or 'Other' should be populated. 'Other' could be 'Alias', 'Proxy' or 'National Account Number'. Important: Either Identification/SchemeName or Identification/Proxy to be used. Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice
	1..1		<i>XML Tag</i>	xs:choice
2.177	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++IBAN	<i>NPC Rulebook</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i> <i>Pattern</i>	AT-20 The IBAN of the account of the Beneficiary. IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.178	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i>	<i>AT-25 The Proxy/Alias of the account of the Beneficiary.</i> <i>When 'Proxy', 'Alias' or 'BBAN' is populated using 'Other', 'SchemeName' must be specified together with code (BBAN) or Proprietary code e.g. SE BGNR.</i> <i>'Other' needs to be included if proxy element (2.187) is used.</i> Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1
2.179	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Identification	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	<i>If 'Proxy' or 'Alias' is provided in the Proxy element state NOTPROVIDED.</i> Identification Identification assigned by an institution. Id Max34Text 1 .. 34 1 .. 34
2.180	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Scheme Name	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	<i>'Proxy', 'Alias' or 'National Account number' schemes defined by Proprietary code (e.g. Swedish Bankgiro number, Swedish Plusgiro number, Danish FIK/Giro, Mobile phone number etc.) or code (e.g. National Account Number). Mandatory if National Account Number (BBAN).</i> Scheme Name Name of the identification scheme. SchmeNm AccountSchemeName1Choice
	1..1		<i>XML Tag</i>	xs:choice
2.181	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Scheme Name +++++Code	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	<i>Code used for National Account Number (BBAN).</i> Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalAccountIdentification1Code 1 .. 4 1 .. 4
2.182	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Scheme Name +++++Proprietary	<i>NPC Usage Rule(s)</i>  <i>ISO Name</i> <i>ISO Definition</i>  <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	<i>Proprietary code are used to define SchemeName.</i> Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.183	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Issuer	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>NPC Length</i>	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.184	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Type	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.185	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Currency	ISO Name ISO Definition       XML Tag Type Pattern	Currency Identification of the currency in which the account is held.  Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.186	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Name	ISO Name ISO Definition       XML Tag Type ISO Length NPC Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.  Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.187	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy	ISO Name ISO Definition  XML Tag Type	Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.188	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy ++++Type	ISO Name ISO Definition XML Tag Type	Type Type of the proxy identification. Tp ProxyAccountType1Choice
	1..1		XML Tag	xs:choice
2.189	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy ++++Type ++++Code	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalProxyAccountType1Code 1 .. 4 1 .. 4
2.190	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy ++++Type ++++Proprietary	NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Proprietary used to define the Proxy (e.g. Swedish Bankgiro number, Swedish Plusgiro number, Danish FIK Code, Mobile phone number etc). Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.191	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy +++++Identification	<i>NPC Usage Rule(s)</i>	'Alias'/'Proxy' defined by Code or Proprietary code (Swedish Bankgiro number, Swedish Plusgironumber etc).
			ISO Name	Identification
			ISO Definition	Identification used to indicate the account identification under another specified name.
			XML Tag	Id
			Type	Max2048Text
			ISO Length	1 .. 2048
			NPC Length	1 .. 2048
2.192	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor	ISO Name	Ultimate Creditor
			ISO Definition	Ultimate party to which an amount of money is due.
			XML Tag	UltmtCdtr
			Type	PartyIdentification135
2.193	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Name	<i>NPC Rulebook</i>	AT-28 The name of the Beneficiary Reference Party.
			<i>NPC Format Rule(s)</i>	'Name' is limited to 70 characters in length.
			ISO Name	Name
			ISO Definition	Name by which a party is known and which is usually used to identify that party.
			XML Tag	Nm
			Type	Max140Text
			ISO Length	1 .. 140
			NPC Length	1 .. 70
2.194	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Postal Address	<i>NPC Usage Rule(s)</i>	If a Postal Address sub-element other than 'Address Line' and 'Country' is used, then 'Address Line' is forbidden. A combination of 'Address Line' and 'Country' is allowed. If 'AddressLine' is not used, then at least 'Town Name' and 'Country' must be used. 'Address Line' is not to be used after 2025. Only structured postal address elements must be used.
			ISO Name	Postal Address
			ISO Definition	Information that locates and identifies a specific address, as defined by postal services.
			XML Tag	PstlAdr
			Type	PostalAddress24
2.195	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Identification	<i>NPC Rulebook</i>	AT-29 The identification code of the Beneficiary Reference Party.
			ISO Name	Identification
			ISO Definition	Unique and unambiguous identification of a party.
			XML Tag	Id
			Type	Party38Choice
	1..1		XML Tag	xs:choice
2.196	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Identification +++++Organisation Identification	<i>NPC Usage Rule(s)</i>	Either 'AnyBIC', 'LEI' or 'Other' is allowed.
			ISO Name	Organisation Identification
			ISO Definition	Unique and unambiguous way to identify an organisation.
			XML Tag	OrgId
			Type	OrganisationIdentification29
2.197	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Identification +++++Private Identification	<i>NPC Usage Rule(s)</i>	Either 'Date and Place of Birth' or 'Other' is allowed.
			ISO Name	Private Identification
			ISO Definition	Unique and unambiguous identification of a person, for example a passport.
			XML Tag	PrvtId
			Type	PersonIdentification13

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.198	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Country Of Residence	ISO Name ISO Definition  XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.199	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Contact Details	ISO Name ISO Definition  XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.200	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Instruction For Creditor Agent	ISO Name ISO Definition  XML Tag Type	Instruction For Creditor Agent Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent. InstrForCdrAgt InstructionForCreditorAgent1
2.201	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Instruction For Debtor Agent	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Instruction For Debtor Agent Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent. InstrForDbtrAgt Max140Text 1 .. 140 1 .. 140
2.202	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Purpose	NPC Rulebook ISO Name ISO Definition  XML Tag Type	AT-44 The purpose of the NPC Credit Transfer. Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
	1..1		XML Tag	xs:choice
2.203	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Purpose ++++Code	NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	In case the transaction is a transfer back related to an earlier executed NPC Credit Transfer (NCT) Transaction, the code must be 'RRCT' (Reimbursement Received Credit Transfer) or another code meaningful for identifying the NCT as a transfer back. 'RRTP' (Related to an RTP) must be used if the NCT is the result of a received Request-to-Pay message. Code Underlying reason for the payment transaction, as published in an external purpose code list. Cd ExternalPurpose1Code 1 .. 4 1 .. 4
2.204	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.205	0..10	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.206	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.207	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7
2.208	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-05 The Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction. In accordance with description in AT-05. Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
2.209	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Unstructured	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	'Unstructured' may carry structured remittance information, as agreed between the Originator and the Beneficiary. Only one occurrence of 'Unstructured' is allowed. "Unstructured" must be present when there are more than one occurrence of Structured remittance information. Unstructured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Ustrd Max140Text 1 .. 140 1 .. 140
2.210	0..999	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured	NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type	Maximum 999 occurrences of 'Structured' is allowed. If more than one occurrence of Structured remittance information, also the Unstructured remittance information must be present, see AT-05 for details. For non-ERI: 'Structured' can be used, provided the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) do not exceed 140 characters in length. For ERI: In each occurrence of 'Structured' the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) must not exceed 280 characters in length. Structured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. Strd StructuredRemittanceInformation16

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.211	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information	ISO Name ISO Definition XML Tag Type	Referred Document Information Provides the identification and the content of the referred document. RfrdDocInf ReferredDocumentInformation7
2.212	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the type of referred document. Tp ReferredDocumentType4
2.213	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Provides the type details of the referred document. CdOrPrtry ReferredDocumentType3Choice
	1..1		XML Tag	xs:choice
2.214	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Code Or Proprietary +++++Code	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only CINV and CREN is allowed. Code Document type in a coded form. Cd DocumentType6Code
			NPC Code Restrictions	
			CINV	CommercialInvoice Document is an invoice.
			CREN	CreditNote Document is a credit note.
2.215	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Code Or Proprietary +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Proprietary identification of the type of the remittance document. Prtry Max35Text 1 .. 35 1 .. 35
2.216	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Identification of the issuer of the reference document type. Issr Max35Text 1 .. 35 1 .. 35
2.217	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Number Unique and unambiguous identification of the referred document. Nb Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.218	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information ++++++Related Date	ISO Name ISO Definition XML Tag Type	Related Date Date associated with the referred document. RltdDt ISODate
2.219	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information ++++++Line Details	ISO Name ISO Definition XML Tag Type	Line Details Set of elements used to provide the content of the referred document line. LineDtls DocumentLineInformation1
2.220	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory when extended remittance information is used. All references must have a referred amount and the sum of the amounts of the referred references must equal the instructed amount of the Credit Transfer.</i> Referred Document Amount Provides details on the amounts of the referred document. RfrdDocAmt RemittanceAmount2
2.221	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Due Payable Amount	ISO Name ISO Definition XML Tag Type <i>NPC FractDigits</i> <i>TotalDigits</i> <i>NPC Inclusive</i>	Due Payable Amount Amount specified is the exact amount due and payable to the creditor. DuePyblAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
2.222	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Discount Applied Amount	ISO Name ISO Definition XML Tag Type	Discount Applied Amount Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor. DscentApldAmt DiscountAmountAndType1
2.223	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Credit Note Amount	ISO Name ISO Definition XML Tag Type <i>NPC FractDigits</i> <i>TotalDigits</i> <i>NPC Inclusive</i>	Credit Note Amount Amount specified for the referred document is the amount of a credit note. CdtNoteAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
2.224	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Tax Amount	ISO Name ISO Definition XML Tag Type	Tax Amount Quantity of cash resulting from the calculation of the tax. TaxAmt TaxAmountAndType1
2.225	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Adjustment Amount And Reason	ISO Name ISO Definition XML Tag Type	Adjustment Amount And Reason Specifies detailed information on the amount and reason of the document adjustment. AdjstmntAmtAndRsn DocumentAdjustment1



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.226	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Remitted Amount	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	Remitted Amount Amount of money remitted for the referred document. RmtdAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
2.227	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	When present, the Debtor PSP is obliged to validate the reference information. When used both 'Creditor Reference Type' and 'Creditor Reference' must be present. Creditor Reference Information Reference information provided by the creditor to allow the identification of the underlying documents. CdtrRefInf CreditorReferenceInformation2
2.228	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory if 'Creditor Reference Information' is used. Type Specifies the type of creditor reference. Tp CreditorReferenceType2
2.229	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice
	1..1		XML Tag	xs:choice
2.230	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary +++++++Code	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'SCOR' is allowed. Code Type of creditor reference, in a coded form. Cd DocumentType3Code
			NPC Code Restrictions	
			SCOR	StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.
2.231	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35



#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.232	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Issuer	<b>NPC Usage Rule(s)</b> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	<i>If RF/Structured Creditor Reference (ISO 11649) is used, type must be 'ISO'.</i> Issuer Entity that assigns the credit reference type. Issr Max35Text 1 .. 35 1 .. 35
2.233	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Reference	<b>NPC Usage Rule(s)</b> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	<i>Mandatory if 'Creditor Reference Information' is used. When present, the Debtor PSP is obliged to validate the reference. Only OCR/KID Reference or RF/Structured Creditor Reference (ISO 11649) is allowed.</i> <i>RF/Structured Creditor Reference can only be used in combination with IBAN and must be used if 'ISO' is stated as 'Issuer'.</i> <i>OCR Reference can only be used in combination with a corresponding 'Proxy'/'Alias'.</i> Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.  Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.  If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification. Ref Max35Text 1 .. 35 1 .. 35
2.234	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Invoicer	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor. Invr PartyIdentification135
2.235	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Invoicee	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor. Invcee PartyIdentification135
2.236	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Tax Remittance	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Tax Remittance Provides remittance information about a payment made for tax-related purposes. TaxRmt TaxInformation7
2.237	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Garnishment Remittance	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes. GrnshmtRmt Garnishment3

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.238	0..3	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Additional Remittance Information	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Additional Remittance Information Additional information, in free text form, to complement the structured remittance information. AddtlRmtInf Max140Text 1 .. 140 1 .. 140
2.239	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Supplementary Data	ISO Name ISO Definition  XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
3.0	0..n	Customer Credit Transfer Initiation V09 +Supplementary Data	ISO Name ISO Definition  XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

## 2.2 PSP to Customer Reject, Negative or Positive response Credit Transfer Dataset (based on DS-03)

Caution: These Guidelines are not sufficient to fully implement this message and require additional information under bilateral agreement between the customer and its PSP. The Rulebook in addition does not specify the dataset requirements.

### 2.2.1 Recommended Use of the Customer Payment Status Report (pain.002.001.10)

The CustomerPaymentStatusReport message pain.002 is used to provide information about the status, positive and/or negative on credit transfer instructions (pain.001) earlier sent. The message caters for bulk and single accept/reject instructions.

The CustomerPaymentStatusReport message includes status on either 'Group Status', 'Payment Information Status' or 'Transaction Status'. A reject status in pain.002, transported between the PSPs and their remitting customers, always includes a status reason code describing the reject reason.

Examples of status codes to be used for each level are provided in this document in section 2.2.2 Message Specifications.

Examples of status reason codes are provided in this document in section 2.2.3 Message Specifications.

Debtor Agent, upon reception of the pain.001, validates the message and produces status report(s) providing information about whether the payment instruction/transactions will be processed or not, i.e., if the file and/or the transactions in the file are rejected or accepted by the Debtor Agent.

There can be several status reports pain.002 produced for one credit transfer pain.001.

The CustomerStatusReport message refers to the original instruction(s) by means of references that links the transaction information in the pain.002 status report to the original pain.001:

pain.002	Link	pain.001
<OrgnlGrpInfAndSts><OrgnlMsgId>	MsgId	<GrpHdr><MsgId>
<GrpHdr><InitgPty><Id><OrgId> <Othr><Id>	InitgPrtyId	<GrpHdr><InitgPty><Id><OrgId> <Othr><Id>
<OrgnlPmtInfAndSts><OrgnlPmtInfId>	PmtInfId	<PmtInf><PmtInfId>
<OrgnlPmtInfAndSts><TxInfAndSts> <OrgnlInstrId>	InstrId	<PmtInf><CdtTrfTxinf> <PmtId> <InstrId>
<OrgnlPmtInfAndSts><TxInfAndSts> <OrgnlEndToEndId>	EndToEndId	<PmtInf><CdtTrfTxinf> <PmtId> <EndToEndId>

**Note:** Attribute AT-R4 'The Settlement Date for the Return' is not applicable to reject instructions.

**Note:** Message elements under 'Original Transaction Reference' sequence are based on DS-01 or DS-02 attributes.

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
		Document	<b>XML Tag Type</b>	Document Document
	1..1	Customer Payment Status Report V10	<b>ISO Name ISO Definition</b>	Customer Payment Status Report V10 Scope The CustomerPaymentStatusReport message is sent by an instructed agent to the previous party in the payment chain. It is used to inform this party about the positive or negative status of an instruction (either single or file). It is also used to report on a pending instruction. <b>XML Tag Type</b> CstmrPmtStsRpt CustomerPaymentStatusReportV10
1.0	1..1	Customer Payment Status Report V10 +Group Header	<b>ISO Name ISO Definition</b>	Group Header Set of characteristics shared by all individual transactions included in the status report message. <b>XML Tag Type</b> GrpHdr GroupHeader86
1.1	1..1	Customer Payment Status Report V10 +Group Header ++Message Identification	<b>ISO Name ISO Definition</b>	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party for a pre-agreed period. <b>XML Tag Type</b> MsgId Max35Text <b>ISO Length</b> 1 .. 35 <b>NPC Length</b> 1 .. 35
1.2	1..1	Customer Payment Status Report V10 +Group Header ++Creation Date Time	<b>ISO Name ISO Definition XML Tag Type</b>	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	Customer Payment Status Report V10 +Group Header ++Initiating Party	<b>NPC Usage Rule(s)</b> <b>ISO Name ISO Definition XML Tag Type</b>	<i>Used to identify PSP (BIC) and Customer who has initiated the original message.</i> Initiating Party Party that initiates the status message. InitgPty PartyIdentification135
1.4	0..1	Customer Payment Status Report V10 +Group Header ++Forwarding Agent	<b>ISO Name ISO Definition XML Tag Type</b>	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain. FwdgAgt BranchAndFinancialInstitutionIdentification6
1.5	0..1	Customer Payment Status Report V10 +Group Header ++Debtor Agent	<b>NPC Rulebook NPC Usage Rule(s)</b> <b>ISO Name ISO Definition XML Tag Type</b>	<i>AT-06 The BIC code of the Originator PSP. Either BIC or Clearing system member identification to be used.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
1.6	0..1	Customer Payment Status Report V10 +Group Header ++Creditor Agent	<b>NPC Rulebook NPC Usage Rule(s)</b> <b>ISO Name ISO Definition XML Tag Type</b>	<i>AT-23 The BIC code of the Beneficiary PSP. Either BIC or Clearing system member Identification to be used.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
2.0	1..1	Customer Payment Status Report V10 +Original Group Information And Status	ISO Name ISO Definition  XML Tag Type	Original Group Information And Status Original group information concerning the group of transactions, to which the status report message refers to. OrgnlGrpInfAndSts OriginalGroupHeader17
2.1	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Message Identification	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Only pain.001.001.09 is allowed. Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Creation Date Time	ISO Name ISO Definition  XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime
2.4	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Number Of Transactions	ISO Name ISO Definition  XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original message. OrgnlNbOfTxs Max15NumericText [0-9]{1,15}
2.5	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Control Sum	ISO Name ISO Definition  XML Tag Type NPC FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original message, irrespective of currencies. OrgnlCtrlSum DecimalNumber 2 18
2.6	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Group Status	NPC Rulebook NPC Usage Rule(s)  ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R1 The type of "R" message. 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with a Code. See Message Element Specifications 2.2.2. Group Status Specifies the status of a group of transactions. GrpSts ExternalPaymentGroupStatus1Code 1 .. 4 1 .. 4
2.7	0..n	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information	NPC Usage Rule(s)  ISO Name ISO Definition  XML Tag Type	'Status Reason Information' must be present in 'Original Group Information And Status', 'Original Payment Information and Status' or 'Transaction Information and Status'. Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
2.8	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Originator	<b>NPC Rulebook</b> <b>NPC Usage Rule(s)</b> <b>NPC Format Rule(s)</b> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	<b>AT-R2</b> The identification of the type of party initiating the “R” message. Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Originator Party that issues the status. Orgtr PartyIdentification135
2.9	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason	<b>NPC Rulebook</b> <b>NPC Usage Rule(s)</b> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	<b>AT-R3</b> The reason code for non-acceptance of the NPC Credit Transfer. Mandatory for status rejected. Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		<b>XML Tag</b>	xs:choice
2.10	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Code	<b>NPC Rulebook</b> <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	See Message Element Specifications 2.2.3 below. Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4
2.11	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Proprietary	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.12	0..n	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Additional Information	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Additional Information Further details on the status reason.  Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
2.13	0..n	Customer Payment Status Report V10 +Original Group Information And Status ++Number Of Transactions Per Status	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Number Of Transactions Per Status Detailed information on the number of transactions for each identical transaction status. NbOfTxPerSts NumberOfTransactionsPerStatus5
3.0	0..n	Customer Payment Status Report V10 +Original Payment Information And Status	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	Original Payment Information And Status Information concerning the original payment information, to which the status report message refers. OrgnlPmtInfAndSts OriginalPaymentInstruction32
3.1	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Original Payment Information Identification	<b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnlPmtInfId Max35Text 1 .. 35 1 .. 35



#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.2	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original payment information group. OrgnlNbOfTxS Max15NumericText [0-9]{1,15}
3.3	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Original Control Sum	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original payment information group, irrespective of currencies. OrgnlCtrlSum DecimalNumber 2 18
3.4	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Payment Information Status	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R1 The type of "R" message. 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with a Code. See Message Element Specifications 2.2.2. Payment Information Status Specifies the status of the payment information group. PmtInfSts ExternalPaymentGroupStatus1Code 1 .. 4 1 .. 4
3.5	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	'Status Reason Information' must be present in 'Original Group Information and Status', 'Original Payment Information and Status' or 'Transaction Information and Status'. Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12
3.6	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Originator	NPC Rulebook NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type	AT-R2 The identification of the type of party initiating the "R" message. Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Originator Party that issues the status. Orgtr PartyIdentification135
3.7	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Reason	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R3 The reason code for non-acceptance of the NPC Credit Transfer. Mandatory for status 'rejected'. Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		XML Tag	xs:choice
3.8	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Reason ++++Code	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	See Message Element Specifications 2.2.3 below. Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.9	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
3.10	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Additional Information	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Additional Information Further details on the status reason.  Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.11	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Number Of Transactions Per Status	ISO Name ISO Definition  XML Tag Type	Number Of Transactions Per Status Detailed information on the number of transactions for each identical transaction status. NbOfTxPerSts NumberOfTransactionsPerStatus5
3.12	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status	ISO Name ISO Definition  XML Tag Type	Transaction Information And Status Provides information on the original transactions to which the status report message refers. TxInfAndSts PaymentTransaction105
3.13	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Identification	NPC Rulebook  ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	AT-R5 The specific reference of the PSP initiating the Reject/Return. Status Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status. Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on. StsId Max35Text 1 .. 35 1 .. 35
3.14	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Instruction Identification	ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
3.15	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original End To End Identification	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition  XML Tag Type ISO Length NPC Length	AT-41 The Originator's reference of the Credit Transfer Transaction. Mandatory. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.16	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
3.17	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Transaction Status	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R1 The type of "R" message. 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with a Code. See Message Element Specifications 2.2.2. Transaction Status Specifies the status of a transaction, in a coded form. TxSts ExternalPaymentTransactionStatus1Code 1 .. 4 1 .. 4
3.18	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	'Status Reason Information' must be present in 'Original Group Information and Status', 'Original Payment Information and Status' or 'Transaction Information and Status'. Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12
3.19	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Originator	NPC Rulebook NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type	AT-R2 The identification of the type of party initiating the "R" message. Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Originator Party that issues the status. Orgtr PartyIdentification135
3.20	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R3 The reason code for non-acceptance of the NPC Credit Transfer. Mandatory for status 'rejected'. Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		XML Tag	xs:choice
3.21	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason +++++Code	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	See Message Element specifications 2.2.3 below. Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4
3.22	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.23	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Additional Information	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Additional Information Further details on the status reason.  Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.24	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Charges Information	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Charges Information Provides information on the charges related to the processing of the rejection of the instruction. Usage: This is passed on for information purposes only. Settlement of the charges will be done separately. ChrsgInf Charges7
3.25	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Tracker Data	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Tracker Data Provides information on the tracking of the interbank transaction related to the payment. TrckrData TrackerData1
3.26	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Acceptance Date Time	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime
3.27	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Account Servicer Reference	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
3.28	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Clearing System Reference	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b> <b>ISO Length</b> <b>NPC Length</b>	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.29	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference	<b>NPC Rulebook</b> <b>NPC Usage Rule(s)</b>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	An exact copy of attributes of the received DS-02 or DS-01 which is being rejected. The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Mandatory to provide Original Transaction Reference if transaction is rejected. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.30	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
3.31	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Amount	NPC Rulebook NPC Format Rule(s) ISO Name ISO Definition XML Tag Type	AT-04 The amount of the NPC Credit Transfer in the relevant Scheme Currencies and the relevant currency code. Amount must be 0.01 or more and 9999999999.99 or less. The fractional part has a maximum of two digits. Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
3.32	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
3.33	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.34	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-07 The Requested Execution Date of the Credit Transfer Instruction. Mandatory. Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.35	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.36	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7



#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.37	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	<i>NPC Rulebook</i>	AT-45 The category purpose of the NPC Credit Transfer. AT-40 The identification code of the Scheme. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.38	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
			<i>NPC Code Restrictions</i>	
			<i>CHK</i>	Cheque Written order to a bank to pay a certain amount of money from one person to another person.
			<i>TRF</i>	CreditTransfer Transfer of an amount of money in the books of the account servicer.
3.39	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.40	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	AT-05 The Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction. Should include an exact copy of attribute AT-05 of the initially sent DS-02 which is rejected. Whereby ERI (Extended Remittance Information) was used only the unstructured remittance information sent by the customer (Originator) to the Beneficiary in the NPC Credit Transfer Instruction should be forwarded. Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.41	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	AT-08 The name of the Originator Reference Party. AT-09 The identification code of the Originator Reference Party. Only 'Party' is allowed. Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.42	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	AT-02 The name of the Originator. AT-03 The address of the Originator. AT-10 The Originator identification code. Only 'Party' is allowed. Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice



#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.43	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	<i>NPC Rulebook</i>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<i>AT-01 The IBAN of the account of the Originator.</i> <i>AT-11 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.44	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	<i>NPC Rulebook</i>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<i>AT-06 The BIC code of the Originator PSP (if present in DS-01).</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.45	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.46	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	<i>NPC Rulebook</i>  <i>NPC Usage Rule(s)</i>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<i>AT-23 The BIC code of the Beneficiary PSP (if present in DS-01).</i> <i>Either BIC or Clearing system member Identification to be used.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.47	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.48	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	<i>NPC Rulebook</i>  <i>NPC Usage Rule(s)</i>  <b>ISO Name</b> <b>ISO Definition</b> <b>XML Tag</b> <b>Type</b>	<i>AT-21 The name of the Beneficiary.</i> <i>AT-22 The address of the Beneficiary.</i> <i>AT-24 The Beneficiary identification code.</i> <i>Only 'Party' is allowed.</i> <i>Mandatory to provide Name if Creditor is used.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.49	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	<i>NPC Rulebook</i>  <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<i>AT-20 The IBAN of the account of the Beneficiary.</i> <i>AT-25 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.50	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	<b>NPC Rulebook</b>  <b>NPC Usage Rule(s)</b> <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<b>AT-28</b> The name of the Beneficiary Reference Party. <b>AT-29</b> The identification code of the Beneficiary Reference Party. Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.51	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Purpose	<b>NPC Rulebook</b> <b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	<b>AT-44</b> The purpose of the NPC Credit Transfer. Purpose Underlying reason for the payment transaction.  Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.52	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Supplementary Data	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
4.0	0..n	Customer Payment Status Report V10 +Supplementary Data	<b>ISO Name</b> <b>ISO Definition</b>  <b>XML Tag</b> <b>Type</b>	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

## 2.2.2 Message Element Specifications for status codes

The list below contains examples of ExternalPaymentGroupStatus1Code for “Group Status”:

ISO Code	ISO Name	Description of Status Code
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACTC	AcceptedTechnical Validation	Authentication and syntactical and semantical validation are successful.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

The list below contains examples of ExternalPaymentGroupStatus1Code for “Payment Information Status”:

ISO Code	ISO Name	Description of Status Code
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACSP	AcceptedSettlement InProcess	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

The list below contains examples of ExternalPaymentTransactionStatus1Code for “Transaction Status”:

ISO Code	ISO Name	Description of Status Code
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACSC	AcceptedSettlementCompletedDebtorAccount	Settlement on the debtor's account has been completed.
ACSP	AcceptedSettlementInProcess	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

### 2.2.3 Message Element Specifications for reason codes

The list below contains examples of reason codes to be used when a pain.002 message is used for other purposes than accepted. In addition to the code, for further clarification, information can be provided as Additional Information.

For a full list of ISO 20022 ExternalStatusReason1Code, visit the external code list page at [www.iso20022.org](http://www.iso20022.org).

ISO Code	ISO Name	Description of Reason Code
AC01	IncorrectAccountNumber	Account identifier incorrect (i.e., invalid IBAN)
AC02	InvalidDebtorAccountNumber	Debtor account number invalid or missing
AC03	Invalid Creditor Account Number	Creditor account number invalid or missing
AC04	ClosedAccountNumber	Account number specified has been closed on the bank of account's books.
AC05	ClosedDebtorAccountNumber	Debtor account number closed
AC07	ClosedCreditorAccountNumber	Creditor account number closed
AG02	InvalidBankOperationCode	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for incorrect operation/transaction code.
AM03	NotAllowedCurrency	Specified message amount is a non-processable currency outside of existing agreement <i>Usage Rule:</i> To be used when Beneficiary PSP is not reachable in the specified currency.
AM04	Insufficient Funds	Amount of funds available to cover specified message amount is insufficient.
AM05	Duplication	Duplicate payment
AM11	InvalidTransactionCurrency	Transaction currency is invalid or missing <i>Usage Rule:</i> To be used when Beneficiary PSP is not reachable for cross border transactions.
CNOR	Creditor bank is not registered	Creditor PSP is not registered under this BIC in the CSM
DNOR	Debtor bank is not registered	Debtor PSP is not registered under this BIC in the CSM
ERIN	ERIOptionNotSupported	The Extended Remittance Information (ERI) option is not supported
FF01	InvalidFileFormat	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for invalid file format.
MS03	NotSpecifiedReasonAgentGenerated	Reason not specified
RC01	BankIdentifierIncorrect	PSP identifier incorrect (i.e., invalid BIC)
RR01	MissingDebtorAccountOrIdentification	Regulatory Reason
RR02	MissingDebtorNameOrAddress	Regulatory Reason
RR03	MissingCreditorNameOrAddress	Regulatory Reason

ISO Code	ISO Name	Description of Reason Code
RR04	RegulatoryReason	Regulatory Reason
RR05	RegulatoryInformationInvalid	Regulatory or Central Bank Reporting information missing, incomplete or invalid.
RR09	InvalidStructuredCreditorReference	Proprietary code for structured creditor reference invalid or missing. Usage rule: To be used when structured reference is invalid or missing.
TM01	CutOffTime	File received after Cut-off Time

### 3 List of changes in the NPC Credit Transfer Customer-to-PSP Implementation Guidelines 2023 version 1.3

(Note: This list is for information – the changes included in the body of the document are the changes in effect)

#### SYMBOLS USED

1. Column one contains the identification number of the Change
2. Column two contains the reference(s) to the relevant Index Number
3. Column three contains the reference(s) to the relevant section or message element
4. Column four contains a description of the change
5. Column five contains a status code:
  - REJ: Rejected by the NCT & NCT Inst WG
  - PEN: Issue pending in the NCT & NCT Inst WG
  - ACC: Accepted by the NCT & NCT Inst WG in Guidelines
6. Column six contains the type of change:
  - TYPO: Typing and layout errors
  - CLAR: Clarification of the text
  - CHAN: Change in or further alignment with the Rulebook content

#### 3.1 List of changes 2023 v 1.3 relative to 2023 v 1.2

N°	#	Section / Message Element	Description	Status	Type
1.	2.1.1	2.43	LEI changed from white to yellow	ACC	CHAN
2.	2.1.1	2.210	Format Rule added for non-ERI for clarification	ACC	CLAR
3.	2.1.1	2.211	Referred Document Information multiplicity changed from 0..n to 0..1	ACC	CHAN

#### 3.2 List of changes 2023 v 1.2 relative to 2023 v 1.1

N°	#	Section / Message Element	Description	Status	Type
4.	2.1.1	2.68	Multiplicity changed to from 0..1 to 1..1 to comply with ISO20022	ACC	CHAN
5.	2.1.1	2.219	Element Line Details added as a red element to be complete	ACC	CHAN



### 3.3 List of changes 2023 v 1.1 relative to 2023 v 1.0

N°	#	Section / Message Element	Description	Status	Type
1.	2.1.1	2.24	Element Address Type changed to white	ACC	CHAN
2.	2.1.1	2.154	Element Address Type changed to white	ACC	CHAN
3.	3.1	N/A	Addition of new table List of changes 2023 v 1.1 relative to 2023 v 1.0	ACC	CHAN

### 3.4 List of changes 2023 v 1.0 relative to 2020 v 1.1

N°	#	Section / Message Element	Description	Status	Type
1.	General		'The term bank has been replaced by PSP'. Changes done throughout the document.	ACC	CHAN
2.	General		Migration to the 2019 version of the ISO 20022 messaging standard. Changes made throughout the document.	ACC	CHAN
3.	General		Charge Bearer codes SHAR and SLEV have been updated with new definitions for clarification, throughout the document.	ACC	CLAR
4.	General		Format rule for amount (Instructed Amount, Interbank Settlement Amount and Amount) added to be consistent.	ACC	CHAN
5.	General		Usage rule for Postal Address/Address Line word 'Component' is replaced by 'Sub-element'	ACC	CHAN
6.	0.3		Addition of Notes (term Bank/PSP and Customer).	ACC	CLAR
7.	1.0		Name of dataset DS-03 changed due to extended scope	ACC	CHAN
8.	1.4		"Including the Scandinavian characters as defined above" taken out under bullet point 5. New note added in last paragraph.	ACC	CHAN
9.	1.5.4		Additional information about Alias/Proxy for clarification.	ACC	CLAR
10.	2		Name of section changed to Recommended PSP to-PSP Messages. Replacement of the wording "BIC or BEI" by the wording "AnyBIC" in the Usage Rule throughout the document. BIC has been replaced with BICFI throughout the document.	ACC	CHAN
11.	2.1.1		Three new notes added	ACC	CHAN
12.	2.1.1	1.5	NPC usage rule removed and multiplicity changed to 0..1	ACC	CHAN
13.	2.1.1	2.2	CHK added under NPC Code restrictions and NPC usage rule updated.	ACC	CHAN
14.	2.1.1	2.5	NPC Fract Digits changed to '2'	ACC	TYPO
15.	2.1.1	2.8	Usage rule for Service Level updated since ISO is unlimited	ACC	CHAN
16.	2.1.1	2.10	Proprietary element changed to white since only NPCA is allowed.	ACC	CHAN
17.	2.1.1	2.16	Proprietary added as white element for consistency reasons	ACC	CHAN
18.	2.1.1	2.18-2.19	Requested execution date added as yellow element and date time added as white element (ISO 2019)	ACC	CHAN
19.	2.1.1	2.23 2.29-2.32 2.35-2.36	Underlying elements for structured address added. Usage rule updated to clarify usage.	ACC	CHAN
20.	2.1.1	2.39	Usage rule updated to clarify usage.	ACC	CHAN
21.	2.1.1	2.41-2.49	Underlying element added for Organisation Identification including LEI as a white element (ISO 2019). Usage rule changed, removal of "one occurrence of other".	ACC	CHAN
22.	2.1.1	2.50-2.61	Underlying elements added for Private Identification	ACC	CHAN
23.	2.1.1	2.64-2.72	Changes made under Debtor account for Proxy/Alias to clarify usage. Name of AT-11 changed to align with EPC. Multiplicity	ACC	CHAN

N°	#	Section / Message Element	Description	Status	Type
			changed to 1..1 for Scheme name code and proprietary. Issuer added as red element.		
24.	2.1.1	2.76-2.80	Proxy including underlying elements added as yellow elements.	ACC	CHAN
25.	2.1.1	2.82	Usage rule 'BICFI is recommended' added.	ACC	CHAN
26.	2.2.1	2.85	LEI added as white element (ISO 2019)	ACC	CHAN
27.	2.1.1	2.94	Instruction of Debtor Agent added as white element (ISO 2019)	ACC	CHAN
28.	2.1.1	2.96	Multiplicity changed to 1..1 for Ultimate Debtor Name. Usage rule added.	ACC	CHAN
29.	2.1.1	2.97	Usage rule added for Postal Address	ACC	CHAN
30.	2.2.1	2.99-2.100	Usage rule changed for Org Id and Private Id (removal of "one occurrence of other").	ACC	CHAN
31.	2.1.1	2.110	UETR added as white element (ISO 2019)	ACC	CHAN
32.	2.1.1	2.113	Usage rule for Service Level updated since ISO is unlimited	ACC	CHAN
33.	2.1.1	2.115	Proprietary element changed to white since only NPCA is allowed.	ACC	CHAN
34.	2.1.1	2.117	Addition of usage rule for 'PERI'	ACC	CHAN
35.	2.1.1	2.121	Proprietary added as yellow element for consistency reasons	ACC	CHAN
36.	2.1.1	2.127	Cheque instruction element changed from red to white	ACC	CHAN
37.	2.1.1	2.129	Multiplicity changed to 1..1 for Ultimate Debtor Name. Usage rule added.	ACC	CHAN
38.	2.1.1	2.130	Usage rule added for Postal Address	ACC	CHAN
39.	2.1.1	2.132-2.133	Usage rule changed for Org Id and Private Id	ACC	CHAN
40.	2.1.1	2.142, 2.144	NPC Rulebook referring to AT-23 moved from Creditor Agent to BICFI	ACC	CHAN
41.	2.1.1	2.145-2.149	NPC usage rule added and underlying elements added to clarify usage.	ACC	CHAN
42.	2.1.1	2.153 2.159-2.162 2.165-2.166	Underlying elements for structured address added. Usage rule updated to clarify usage.	ACC	CHAN
43.	2.1.1	2.169	Usage rule updated to clarify usage.	ACC	CHAN
44.	2.1.1	2.171-2.172	Usage rule changed for Org Id and Private Id	ACC	CHAN
45.	2.1.1	2.175-2.183	Changes made under Creditor account for Proxy/Alias to clarify usage. Name of AT-25 changed to align with EPC. Multiplicity changed to 1..1 for IBAN and Identification, Scheme name code and proprietary. Issuer added as red element.	ACC	CHAN
46.	2.1.1	2.184	Addition of white element to align with EPC.	ACC	CHAN
47.	2.1.1	2.185	Currency added as yellow element (ISO 2019)	ACC	CHAN

N°	#	Section / Message Element	Description	Status	Type
48.	2.1.1	2.186	Name added as white element for consistency reasons	ACC	CHAN
49.	2.1.1	2.187- 2.191	Proxy including underlying elements added as yellow elements.	ACC	CHAN
50.	2.1.1	2.194	Usage rule updated under Postal Address to clarify usage.	ACC	CHAN
51.	2.1.1	2.196- 2.197	Usage rule changed for Org Id and Private Id	ACC	CHAN
52.	2.1.1	2.202- 2.203	Usage rule moved from Purpose to Code.	ACC	CHAN
53.	2.1.1	2.212	Multiplicity changed to 1..1	ACC	CHAN
54.	2.1.1	2.215	Addition of 'Proprietary' element shaded red for consistency reason.	ACC	CHAN
55.	2.1.1	2.217- 2.218	Number and Related Date added as yellow elements	ACC	CHAN
56.	2.1.1	2.219- 2.225	Addition of underlying elements for Referred Document Amount.	ACC	CHAN
57.	2.1.1	2.232	NPC usage rule under Reference changed to be correct and clarify usage for the Nordics.	ACC	CHAN
58.	2.1.1	2.235- 2.236	Tax Remittance and Garnishment Remittance added as white elements (ISO 2019)	ACC	CHAN
59.	2.1.1	2.237	Additional Remittance Information changed to yellow	ACC	CHAN
60.	2.1.1	2.238, 3.0	Supplementary data added as white elements (ISO 2019)	ACC	CHAN
61.	2.2.1		Name of DS-03 changed due to extended scope	ACC	CHAN
62.	2.2.1	2.2.1	Initial text updated due to extended scope	ACC	CHAN
63.	2.2.1	1.3	NPC usage added and element changed to yellow	ACC	CHAN
64.	2.2.1	2.6	Usage rule updated and NPC code restrictions removed.	ACC	CHAN
65.	2.2.1	2.8	Usage rule 'mandatory' removed. Multiplicity changed to 0..1.	ACC	CHAN
66.	2.2.1	2.9	Multiplicity changed to 0..1	ACC	CHAN
67.	2.2.1	2.10	Message Specifications for reason code changed to 2.2.3	ACC	CHAN
68.	2.2.1	2.12	Additional Information changed to yellow	ACC	CHAN
69.	2.2.1	3.3	Fract digits changed to '2'	ACC	TYPO
70.	2.2.1	3.4	Usage rule updated and NPC code restrictions removed.	ACC	CHAN
71.	2.2.1	3.6	Usage rule 'mandatory' removed. Multiplicity changed to 0..1.	ACC	CHAN
72.	2.2.1	3.7	Multiplicity changed to 0..1	ACC	CHAN
73.	2.2.1	3.8	Message Specifications for reason code changed to 2.2.3	ACC	CHAN
74.	2.2.1	3.10	Additional Information changed to yellow	ACC	CHAN
75.	2.2.1	3.15	Original End to End Identification multiplicity changed to 1..1	ACC	CHAN
76.	2.2.1	3.17	Usage rule updated and NPC code restrictions removed.	ACC	CHAN
77.	2.2.1	3.19	Usage rule 'mandatory' removed. Multiplicity changed to 0..1.	ACC	CHAN

N°	#	Section / Message Element	Description	Status	Type
78.	2.2.1	3.20	Multiplicity changed to 0..1	ACC	CHAN
79.	2.2.1	3.21	Message Specifications for reason code changed to 2.2.3	ACC	CHAN
80.	2.2.1	3.23	Additional Remittance Information changed to yellow	ACC	CHAN
81.	2.2.1	3.25	Tracker Data added as white element (ISO 2019)	ACC	CHAN
82.	2.2.1	3.29	Usage rule under Original Transaction Reference updated	ACC	CHAN
83.	2.2.1	3.31	Multiplicity for Amount changed to 1..1	ACC	CHAN
84.	2.2.1	3.34	Multiplicity for Requested Execution Date changed to 1..1	ACC	CHAN
85.	2.2.1	3.38	CHK added under NPC Code restrictions	ACC	CHAN
86.	2.2.1	3.43	Name of AT-11 changed under Debtor Account changed to align with EPC.	ACC	CHAN
87.	2.2.1	3.48	NPC Usage Rule for Creditor updated. Multiplicity changed to 0..1.	ACC	CHAN
88.	2.2.1	3.49	AT-25 added under Creditor Account	ACC	CHAN
89.	2.2.1	3.41, 3.42 3.48, 3.50	NPC Usage Rule 'Only party is allowed' added.	ACC	CHAN
90.	2.2.1	3.51	Purpose added as yellow element (ISO 2019)	ACC	CHAN
91.	2.2.1	3.52, 4.0	Supplementary data added as white elements (ISO 2019)	ACC	CHAN
92.	2.2.2		New section for Status Codes added	ACC	CHAN
93.	2.2.3		Section 2.2.2 changed to 2.2.3. Text updated due to extended scope. New reason codes added to the list: AC02, AC03, AC04, AC05, AC07, AM04, RR05.	ACC	CHAN