

NPC INSTANT CREDIT TRANSFER SCHEME CUSTOMER-TO-PSP RECOMMENDED IMPLEMENTATION GUIDELINES

NPC013-01 / 2025 Version 1.0 / Date issued: 05 December 2024 / Date effective: 05 October 2025

Public

Abstract

This document sets out the recommended rules for implementing the 2025 NPC Instant Credit Transfer Scheme Rulebook based on version 2019 of the customer-to-PSP credit transfer ISO 20022 XML message standards.

TABLE OF CONTENTS

0. Document Information	3
0.1 References	3
0.2 Change History	4
0.3 Purpose of Document	4
1. Introduction	5
1.1 Coverage of the NPC customer-to-PSP Implementation Guidelines	5
1.2 Use of these Guidelines by the instructing and instructed parties	6
1.3 Notation Conventions	7
1.4 Character Set	8
1.5 General Message Element Specifications	9
1.5.1 BIC	9
1.5.2 Currency	9
1.5.3 Alias and Proxy	9
1.5.4 Structured creditor references, e.g. OCR-references	9
1.6 Implementation of ISO 20022 XML rules	9
2. Recommended Customer-to-PSP and PSP-to-Customer messages	10
2.1 Customer to PSP Credit Transfer Information (DS-01)	10
2.1.1 Use of the Customer Credit Transfer Initiation (pain.001.001.09)	10
2.1.2 Message Element Specifications	49
2.2 PSP to Customer Reject, Negative or Positive Confirmation (based on DS-03)	50
2.2.1 Recommended Use of the Customer Payment Status Report (pain.002.001.10)	50
2.2.2 Message Element Specifications status code	62
2.2.3 Message Element Specifications	63
2.3 Positive Notification Message to the Beneficiary (DS-10)	65
2.3.1 Use of the PSP-to-Customer Debit Credit Notification (camt.054.001.08)	65
3. List of changes in the NPC Instant Credit Transfer Customer-to-PSP Implementation Guidelines 2025 version 1.0	92
3.1 List of changes 2025 v 1.0 relative to 2023 v 1.3	92

0. Document Information

0.1 References

This section lists relevant documents of interest.

	Document Number	Title	Issued by:
[1]	NPC010-01	NPC Instant Credit Transfer Scheme Rulebook 2023 Version 1.0	NPC
[2]	-	ISO 20022 XML Credit Transfers and Related Messages: <ul style="list-style-type: none"> Initiation Credit Notification Note: The 2023 IGs are based on the 2019 message version of ISO 20022.	<u>ISO 20022</u>
[3]	ISO 3166	Country Codes	ISO
[4]	ISO 4217	Currency Code List	ISO
[5]	ISO 9362	Business Identifier Codes (BIC)	ISO
[6]	ISO 13616	IBAN: International Bank Account Number	ISO ¹
[7]	ISO 11649	Structured creditor reference to remittance information	ISO
[8]	EPC230-15	Clarification Paper on the Use of Slashes in References, Identifications and Identifiers	EPC
[9]	NPC100-01	NPC Scheme Currencies – currencies covered by the Scheme	NPC
[10]	NPC014-01	Maximum Amount for Instructions under the NPC Instant Credit Transfer Scheme Rulebook	NPC

¹ See also http://www.swift.com/products/bic_registration/iban_format_registration

0.2 Change History

Issue number	Dated	Reason for revision
2021 v.1.0	2020-03-27	Decided by NPC Scheme Management Committee (SMC) 26 Mars 2020.
2021 v.1.0.1	2020-09-09	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 10 June 2020. All changes listed in in chapter 3.
2021 v.1.1	2021-04-30	Updates agreed by NCT & NCT Inst and decided by the NPC Scheme Management Committee (SMC) 13 April 2021.
2023 v.1.0	2022-07-11	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 8 June 2022. All changes listed in in chapter 3.
2023 v.1.1	2022-12-06	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 24 November 2022. All changes listed in in chapter 3.
2023 v.1.2	2023-04-17	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 17 April 2023. All changes listed in in chapter 3.
2023 v.1.3	2023-11-27	Updates suggested by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 23 November 2023. All changes listed in in chapter 3.
2025 v.1.0	2024-12-05	Updates suggested by NPC TF IG, agreed by NCT & NCT Inst WG and decided by the NPC Scheme Management Committee (SMC) 20 November 2024. All changes listed in in chapter 3.

0.3 Purpose of Document

The objective of these Guidelines is to define the recommended rules to be applied to the ISO 20022 XML message standards for the implementation of the NPC instant credit transfers (NCT Inst) in the customer-to-Payment Service Provider (C2PSP) space.

Note: The term “bank” has been replaced by “PSP” in all the NPC payment scheme rulebooks and associated implementation guidelines to formally reflect the changes introduced by the Payment Services Directive (PSD) to the categories of institutions that can offer payment services, and the variety in PSP categories that are eligible to adhere to the NPC payment schemes. However, please note that in the context of ISO, the term “bank” is still used.

Note: The term ‘Customer’ is to be understood as ‘Payment Service User’ (PSU), meaning a natural or legal person making use of a payment service in the capacity of payer, payee, or both. Such person can take up the role of Originator and/or Beneficiary under the Scheme.”

1. Introduction

This document sets out the NPC recommended rules for implementing the credit transfer ISO 20022 XML initiation message standards. The NPC Instant Credit Transfer Scheme Rulebook defines data sets which are implemented in the relevant ISO 20022 XML message standard of which the following are covered:

NPC Instant Credit Transfer Scheme Rulebook	ISO 20022 XML Message Standards
DS-01 <i>Customer to PSP Credit Transfer Information</i>	Customer Credit Transfer Initiation (pain.001.001.09)
DS-04 <i>PSP to Customer NCT Inst Credit Transfer dataset</i>	Statements/advice ISO 20022 XML standards are covered separately.
<i>Reject, Negative or positive confirmation based on DS-03 Confirmation Message to Originator PSP</i>	Customer Payment Status Report (pain.002.001.10)
<i>DS-10 Positive Notification Message to the Beneficiary</i>	Bank-To-Customer - Debit Credit Notification V08 (camt.054.001.08)

The Guidelines for the customer-to-PSP and PSP-to-customer XML message standards are a recommendation from the NPC on how to support the XML message standards at the request of the Originator or Beneficiary. This means that a Scheme Participant is recommended to accept the messages as described in these guidelines.

1.1 Coverage of the NPC customer-to-PSP Implementation Guidelines

The purpose of the NPC customer-to-PSP Implementation Guidelines, hereafter referred to as the Guidelines, is to provide guidance on the use of the payment initiation ISO 20022 XML standards (the 'pain' messages) in initiating NPC core payments as defined in the NPC scheme rulebooks and supplemented by processing requirements.

The Guidelines are fully aligned to the NPC core requirements when defined in the Rulebook and identify message elements needed for initiating NPC payments while recognizing message elements that may be available for use in Additional Optional Services (AOS), as shown below.

Global ISO 20022 XML Message Standards			
Message elements from the ISO messages corresponding to Rulebook requirements	Message elements that are mandatory in the ISO messages or needed for Processing	Message elements from the ISO messages available for use by AOS within an NPC Governance framework	Message elements from ISO messages not applicable to NPC
NPC Implementation Guidelines for NPC Core subset, identifying elements <ul style="list-style-type: none"> - to be used as defined in ISO - to be used with NPC usage rules (from or completing the Rulebook) Note: yellow fields can be used in a specific way for an AOS.		To be developed and documented by AOS Communities	Not available for use in NPC payments
NPC Payments			

Figure 1

These Guidelines define the NPC Core Mandatory Subset² of the Global ISO 20022 XML standard that consists of message elements:

- required in the Rulebook as business requirements
- needed for processing by PSPs, clearing and settlement mechanisms and PSP customers

Elements needed for specific national regulatory requirements are not considered in these guidelines. They have to be dealt with at national level without being regarded as an AOS.

These message elements define the **NPC core service** and are denoted by yellow shading in the message structures given in the following chapters. Only these elements are further detailed with relevant NPC core requirements, such as the use of the message element, its components or the values that must be used. Usage rules, for example, may indicate limits on the number of repetitions, or code value restrictions, while format rules may be used to indicate the allowable combinations of components of a message element.

These Guidelines also recognize message elements and the usage rules in the ISO 20022 XML standard that may be available for use in an AOS, subject to a governance framework to be defined by the NPC. The definition and documentation of these message elements are a matter for the AOS communities involved. These message elements are denoted by white shading.

Where there are message elements that do not apply to NPC payments, these are denoted with red shading in the right-most column of the message structures. To date, few such message elements have been identified.

1.2 Use of these Guidelines by the instructing and instructed parties³

- NPC core payments are executed using messages only containing message elements defined as part of the NPC Core Subset (shaded yellow in Figure 2).
- Payments that include message elements that are defined and documented by AOS communities (shaded white/yellow in Figure 2) are considered as NPC payments, but not as NPC core payments.

² The NPC Core Mandatory Subset is hereafter known as the NPC core service.

³ Instructing and instructed parties include CSMs.

- It is the responsibility of the instructing customer and instructed PSP of the message to ensure that message elements defined for use in an AOS are only included in messages sent to AOS community members.
- The instructed PSP receiving a message containing AOS message elements, but which is not a member of this AOS community, may ignore the information, that is, not use it for processing, nor forward it to the next party in the chain. The instructed PSP, however, may reject the message for this reason.

1.3 Notation Conventions

The Guidelines are presented in a similar format than the one used in the ISO 20022 XML standard.

#	NPC Mul	Message Element	NPC Core Requirements
1.00	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2	<i>NPC Usage Rule(s)</i> (e.g. Mandatory) <i>NPC Format Rule(s)</i> ISO Name ISO Definition XML Tag Type (Yellow: Message Element that is part of the NPC Core Service)
	1..1		XML Tag xs:choice
1.01	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>NPC Rulebook</i> (Attribute used in Rulebook) <i>NPC Usage Rule(s)</i> (e.g. Only 'NPCA' is allowed.) ISO Name ISO Definition XML Tag Type ISO Length NPC Length (Yellow: Message Element that is part of the NPC Core Service)
			NPC Code restrictions
			NPCA <i>Nordic Payments Council Area Transfer, payments must be executed following the NPC Area Payment Schemes.</i>
1.02	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	ISO Name ISO Definition XML Tag Type (White: Message Element that is not part of the Core Service but is available for use in an NPC AOS)
1.0n	0..1	Message root +Group Header ++Sublevel 1	ISO Name ISO Definition XML Tag Type (Red: Message Element that is not to be used in NPC Payments)

Figure 2

Where:

- Column 1 indicates the message element Index number specific to these Implementation Guidelines. As a result, the Index numbers differ from the ones used in the relating ISO 20022 Message Definition Report, PDF version.

Components of message elements that are not allowed in NPC payments or where no NPC requirements are defined are not displayed in full as the ISO 20022 XML standard applies.

- Column 2 indicates the mandatory or optional status and the number of repetitions defined by the NPC Core Requirements, e.g.:
 - 0..1 element is optional and may only be present once

- 0..n element is optional with unlimited repetition
- 1..1 element is mandatory and must be present exactly once
- 1..n element is mandatory with unlimited repetition

The displayed NPC multiplicity may thus differ from the one of the ISO 20022 XML standard. When an element is shaded yellow, possible remaining ISO 20022 occurrences are available for use in an AOS.

Empty elements are not allowed (i.e. a message shall not contain elements without content).

- Column 3 indicates the full path of an element where the last line contains the name of the message element as defined in the ISO 20022 XML standard. When an element contains sub-elements, these are indented to the right and noted with a plus sign (+) per level.
- Column 4 specifies in italic characters the NPC Core Requirements as additional rules to those specified in the ISO 20022 XML standard, which are shown in non-italic characters.
 - When defined in the Rulebook, the attribute is indicated by the attribute name and where applicable, the number, i.e., AT-nn. Those message elements are shaded yellow.
 - When the message element relates to inter-PSP processing requirements, it is shaded yellow.
 - When the message element specified in the ISO 20022 XML standard is used for NPC payments without change (regarding the definition and any usage rules), no specific NPC Core requirements are provided and is shaded yellow.
 - When the message element is specified in the ISO 20022 XML standard as optional, but is mandatory in NPC Core requirements, this is specified as 'Mandatory' and is shaded yellow.
 - When the message element is not available for use in NPC payments, this is indicated with red shading. Note that these message elements are similarly not available for use in an AOS.
 - The NPC length is indicated for every message element (if applicable), even if it is the same length as in the ISO 20022 XML standard.

Column 4 may also indicate conditional relationships between components of a message element, for example, either component 1 or component 2 must be present, but not both (indicated, in empty lines without index number, in the column 4 with XML Tag 'xs:choice'). In such case, the choice is to be made between the two following sub-elements, if both are shaded yellow.

1.4 Character Set

The character set issue centres on the use of the full set characters in the message elements. Two considerations are:

- While PSPs and their customers must be allowed to use the character set currently in use at national level,
- PSPs and their customers cannot be required to support the full character set used in ISO 20022 XML messages.

Therefore:

- The ISO 20022 XML messages allow for the full range of global language requirements (UTF-8).
- PSPs and their customers must be able to support the Latin character set commonly used in international communication and in addition to this the Scandinavian characters and the @-sign, as follows:

a b c d e f g h i j k l m n o p q r s t u v w x y z å ä ö æ ø
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z Å Ä Ö Æ Ø

0 1 2 3 4 5 6 7 8 9

/ - ? : () . , ' + @

Space

- References, identifications and identifiers must respect the following [8]:
 - Content is restricted to the Latin character set as defined above
 - Content must not start or end with a '/'
 - Content must not contain '//s

Note: When a slash is used as delimiter between the attribute number (AT-XX) or code (ABCD) and the data content, no space is allowed directly after this slash.

However, there may be bilateral or multilateral agreements to support one or more sets of characters beyond the Latin character set including the Scandinavian characters and the @-sign referred to above.

1.5 General Message Element Specifications

1.5.1 BIC

The BIC used to identify financial institutions (Agents in the ISO 20022 XML standards) may be either BIC 11 or BIC 8.

1.5.2 Currency

Unlike EPC/NPC Rulebook, NPC Instant Credit Transfer Rulebook allows more than one currency. Currencies covered by the scheme are called 'Scheme Currencies' and are listed in the reference document *Scheme Currencies* [9].

1.5.3 Alias and Proxy

In the Nordic payment market it is common that an 'Alias' or 'Proxy' is used to identify an Originator's and/or a Beneficiary's account. Therefore, ISO 20022 elements in the Debtor Account and Creditor Account sections are utilized in order to enable (Originators) to initiate their payment from – and to – an 'Alias' or 'Proxy' instead of an IBAN, and for Beneficiaries to still be able to collect payments through an 'Alias' or 'Proxy' instead of their IBAN. NPC usage is described in the NPC Credit Transfer Scheme Inter-PSP Implementation Guideline in the Debtor Account and Creditor Account sections. Attribute AT-P003 Originator Proxy/Alias and AT-E003 Beneficiary Proxy/Alias should be used.

1.5.4 Structured creditor references, e.g. OCR-references

In the Nordic payment market, there is a legacy in some countries to use existing national rules for creditor reference (i.e. OCR-references or Norwegian KID). The different national creditor rules have solutions for maintaining and performing necessary distribution of validation rules for the creditor reference.

Therefore, when Originators have entered a structured reference, it is mandatory that the Originator PSP validates the 'structured creditor reference' by validating according to ISO 11649 (reference [7]) or the respective national creditor reference rules, to ensure the correctness of the structured reference is used

1.6 Implementation of ISO 20022 XML rules

This document should be read in conjunction with the ISO 20022 XML message standards.

2 Recommended Customer-to-PSP and PSP-to-Customer messages

2.1 Customer to PSP Credit Transfer Information (DS-01)

2.1.1 Use of the Customer Credit Transfer Initiation (pain.001.001.09)

The message is used to transport the customer-to-PSP NCT Inst information sent by the Originator to the Originator PSP.

The message caters for bulk and single payment instructions

Note: In case the transaction is a transfer back related to an earlier executed NCT Inst Transaction (as per 'Remarks' under DS-01), the 'purpose' element must be populated with 'RRCT' (Reimbursement Received Credit Transfer) or another code meaningful for identifying the NCT Inst as a transfer back.

Note: In case the transaction is the result of a received Request-to-Pay (RTP) message, the 'Purpose' element must be populated with 'RRTP' (Related to a Request-to-Pay (RTP)). Further details on the RTP are to be found in the SRTP scheme documentation.

Note: The use of NCT Inst is implied by element 'local instrument' being mandatory and 'code' set to 'INST' (Instant Credit Transfer) only.

Note: In case AT-P003 The Proxy/Alias of the account of the Originator or AT-E003 The Proxy/Alias of the account of the Beneficiary is used, there are two alternatives for how to state Proxy/Alias:

1. To state the Proxy/Alias under Proxy element as a Code or Proprietary Code.

2. To state the Proxy/Alias under SchemeName as a Proprietary Code.

Note: In case AT-D003 The BBAN or National account number of the Originator or AT-C003 The BBAN or National account number of the Beneficiary is used, Scheme Name and Code must be used.

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Customer Credit Transfer Initiation V09	ISO Name ISO Definition	Customer Credit Transfer Initiation V09 Scope The CustomerCreditTransferInitiation message is sent by the initiating party to the forwarding agent or debtor agent. It is used to request movement of funds from the debtor account to a creditor.
			XML Tag Type	CstmrCdtTrfInitn CustomerCreditTransferInitiationV09
1.0	1..1	Customer Credit Transfer Initiation V09 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the message.
			XML Tag Type	GrpHdr GroupHeader85
1.1	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.
			XML Tag Type	MsgId
			ISO Length	Max35Text 1 .. 35
			NPC Length	1 .. 35
1.2	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created.
			XML Tag Type	CreDtTm ISODateTime
1.3	0..2	Customer Credit Transfer Initiation V09 +Group Header ++Authorisation	ISO Name ISO Definition	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message. Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party.
			XML Tag Type	Authstn Authorisation1Choice
1.4	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Number Of Transactions	NPC Usage Rule(s)	The validation of this data element depends on pre-agreed customer-to-PSP conditions.
			ISO Name ISO Definition	Number Of Transactions Number of individual transactions contained in the message.
			XML Tag Type	NbOfTx
			Pattern	Max15NumericText [0-9]{1,15}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
1.5	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Control Sum	NPC Usage Rule(s) <i>The validation of this data element depends on pre-agreed customer-to-PSP conditions.</i> NPC Format Rule(s) <i>The fractional part has a maximum of two digits.</i> ISO Name Control Sum ISO Definition Total of all individual amounts included in the message, irrespective of currencies. XML Tag CtrlSum Type DecimalNumber NPC FractDigits 2 TotalDigits 18	
1.6	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party	ISO Name Initiating Party ISO Definition Party that initiates the payment. Usage: This can either be the debtor or the party that initiates the credit transfer on behalf of the debtor. XML Tag InitgPty Type PartyIdentification135	
1.7	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Name	ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party. XML Tag Nm Type Max140Text ISO Length 1 .. 140 NPC Length 1 .. 140	
1.8	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Postal Address	ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services. XML Tag PstlAdr Type PostalAddress24	
1.9	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Identification	ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party38Choice	
	1..1		XML Tag xs:choice	
1.10	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Identification ++++Organisation Identification	NPC Usage Rule(s) <i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification29	
1.11	1..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Identification ++++Private Identification	NPC Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, for example a passport. XML Tag PrvtId Type PersonIdentification13	
1.12	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Country Of Residence	ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}	
1.13	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Initiating Party +++Contact Details	ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party. XML Tag CtctDtls Type Contact4	

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
1.14	0..1	Customer Credit Transfer Initiation V09 +Group Header ++Forwarding Agent	ISO Name ISO Definition XML Tag Type	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution. FwdgAgt BranchAndFinancialInstitutionIdentification6
2.0	1..n	Customer Credit Transfer Initiation V09 +Payment Information	ISO Name ISO Definition XML Tag Type	Payment Information Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation. PmtInf PaymentInstruction30
2.1	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Payment Information Identification Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message. PmtInfId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Method	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'TRF' is allowed. Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod3Code
			NPC Code Restrictions	
			TRF	CreditTransfer Transfer of an amount of money in the books of the account servicer.
2.3	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Batch Booking	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	If present and contains 'true', batch booking is requested. If present and contains 'false', booking per transaction is requested. If element is not present, pre-agreed customer-to-PSP conditions apply. Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
2.4	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Number Of Transactions	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type Pattern	The validation of this data element depends on pre-agreed customer-to-PSP conditions. Number Of Transactions Number of individual transactions contained in the payment information group. NbOfTxS Max15NumericText [0-9]{1,15}
2.5	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Control Sum	NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits	The validation of this data element depends on pre-agreed customer-to-PSP conditions. The fractional part has a maximum of two digits. Control Sum Total of all individual amounts included in the group, irrespective of currencies. CtrlSum DecimalNumber 2 18

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.6	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information	NPC Usage Rule(s)	<i>'Payment Type Information' must be present either here or under 'Credit Transfer Transaction Information'.</i>
			ISO Name	Payment Type Information
			ISO Definition	Set of elements used to further specify the type of transaction.
			XML Tag	PmtTpInf
			Type	PaymentTypeInformation26
2.7	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Instruction Priority	NPC Usage Rule(s)	<i>If present, pre-agreed customer-to-PSP conditions apply. Based on whether priority processing vs. normal processing is offered by the PSP.</i>
			ISO Name	Instruction Priority
			ISO Definition	Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.
			XML Tag	InstrPrty
			Type	Priority2Code
2.8	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Service Level	NPC Usage Rule(s)	<i>Usage is recommended. Only one occurrence is allowed.</i>
			ISO Name	Service Level
			ISO Definition	Agreement under which or rules under which the transaction should be processed.
			XML Tag	SvcLvl
			Type	ServiceLevel8Choice
	1..1		XML Tag	xs:choice
2.9	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Service Level ++++Code	NPC Rulebook	<i>AT-T001 The identification code of the NCT Inst Scheme.</i>
			NPC Usage Rule(s)	<i>Only 'NPCA' is allowed.</i>
			ISO Name	Code
			ISO Definition	Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.
			XML Tag	Cd
			Type	ExternalServiceLevel1Code
			ISO Length	1 .. 4
			NPC Length	1 .. 4
			NPC Code Restrictions	
			NPCA	<i>NordicPaymentsCouncilAreaTransfer Payments must be executed following the NPC Area Payment scheme.</i>
2.10	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Service Level ++++Proprietary	ISO Name	Proprietary
			ISO Definition	Specifies a pre-agreed service or level of service between the parties, as a proprietary code.
			XML Tag	Prtry
			Type	Max35Text
			ISO Length	1 .. 35
			NPC Length	1 .. 35
2.11	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Local Instrument	ISO Name	Local Instrument
			ISO Definition	User community specific instrument.
				Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.
			XML Tag	LclInstrm
			Type	LocalInstrument2Choice
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.12	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Local Instrument ++++Code	NPC Usage Rule(s) Only 'INST' is allowed. ISO Name Code ISO Definition Specifies the local instrument, as published in an external local instrument code list. XML Tag Cd Type ExternalLocalInstrument1Code ISO Length 1 .. 35 NPC Length 1 .. 35	
			NPC Code Restrictions	
			INST	InstantCreditTransfer Transaction is related to an Instant Credit Transfer. Use case example: NCT Instant Credit Transfer (NCT Inst).
2.13	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Local Instrument ++++Proprietary	ISO Name Proprietary ISO Definition Specifies the local instrument, as a proprietary code. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 NPC Length 1 .. 35	
2.14	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Category Purpose	NPC Rulebook AT-T008 The category purpose of the NCT Inst Instruction. NPC Usage Rule(s) If provided by the Originator the Originator PSP, must forward the 'Category Purpose' to the Beneficiary PSP. ISO Name Category Purpose ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain. XML Tag CtgPurp Type CategoryPurpose1Choice	
	1..1		XML Tag	xs:choice
2.15	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Category Purpose ++++Code	ISO Name Code ISO Definition Category purpose, as published in an external category purpose code list. XML Tag Cd Type ExternalCategoryPurpose1Code ISO Length 1 .. 4 NPC Length 1 .. 4	
2.16	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Payment Type Information +++Category Purpose ++++Proprietary	ISO Name Proprietary ISO Definition Category purpose, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 NPC Length 1 .. 35	
2.17	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Requested Execution Date	NPC Rulebook AT-T013 The Requested Execution Date and Time of the NCT Inst Instruction. ISO Name Requested Execution Date ISO Definition Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. XML Tag ReqdExctnDt Type DateAndDateTime2Choice	
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.18	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Requested Execution Date +++Date	ISO Name ISO Definition XML Tag Type	Date Specified date. Dt ISODate
2.19	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Requested Execution Date +++Date Time	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only UTC time format or local time with UTC offset format can be used. Date Time Specified date and time. DtTm ISODateTime
2.20	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Pooling Adjustment Date	ISO Name ISO Definition XML Tag Type	Pooling Adjustment Date Date used for the correction of the value date of a cash pool movement that has been posted with a different value date. PoolgAdjstmntDt ISODate
2.21	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification135
2.22	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Name	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-P001 The name of the Originator. Mandatory. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140
2.23	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-P005 The address of the Originator STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address Line' is mandatory. UNSTRUCTURED ADDRESS: (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid address will be allowed - based on available information at the moment of publication). At least one occurrence of 'Address Line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.24	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.25	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.26	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.27	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.28	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.29	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.30	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.31	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.32	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70
2.33	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.34	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.35	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.36	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	District Name Identifies a subdivision within a country sub-division. DstrctNm Max35Text 1 .. 35 1 .. 35
2.37	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.38	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.39	0..2	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Postal Address ++++Address Line	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Up to two occurrences are allowed. Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.40	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-P004 The Originator identification Code. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.41	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' or 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.42	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Any BIC	ISO Name ISO Definition XML Tag Type Pattern	Any BIC Business identification code of the organisation. AnyBIC AnyBICDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.43	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identification as an alternate identification for a party. LEI LEIIdentifier [A-Z0-9]{18,18}[0-9]{2,2}
2.44	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an organisation, as assigned by an institution, using an identification scheme. Othr GenericOrganisationIdentification1
2.45	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other +++++Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Identification Identification assigned by an institution. Id Max35Text 1 .. 35 1 .. 35
2.46	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other +++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm OrganisationIdentificationSchemeName1Choice
	1..1		XML Tag	xs:choice
2.47	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other +++++Scheme Name +++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalOrganisationIdentification1Code 1 .. 4 1 .. 4
2.48	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other +++++Scheme Name +++++Proprietary	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Reference to ISO 20022 Clarification paper AML codes used in Norway. Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.49	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Organisation Identification +++++Other +++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.50	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.51	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth	ISO Name ISO Definition XML Tag Type	Date And Place Of Birth Date and place of birth of a person. DtAndPlcOfBirth DateAndPlaceOfBirth1

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.52	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++Birth Date	ISO Name ISO Definition XML Tag Type	Birth Date Date on which a person is born. BirthDt ISODate
2.53	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++Province Of Birth	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Province Of Birth Province where a person was born. PrvcOfBirth Max35Text 1 .. 35 1 .. 35
2.54	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++City Of Birth	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	City Of Birth City where a person was born. CityOfBirth Max35Text 1 .. 35 1 .. 35
2.55	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Date And Place Of Birth ++++++Country Of Birth	ISO Name ISO Definition XML Tag Type Pattern	Country Of Birth Country where a person was born. CtryOfBirth CountryCode [A-Z]{2,2}
2.56	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of a person, as assigned by an institution, using an identification scheme. Othr GenericPersonIdentification1
2.57	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
2.58	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm PersonIdentificationSchemeName1Choice
	1..1		XML Tag	xs:choice
2.59	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Scheme Name +++++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalPersonIdentification1Code 1 .. 4 1 .. 4

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.60	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Scheme Name +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.61	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Identification ++++Private Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.62	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.63	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.64	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-D001 The IBAN of the account of the Originator AT-D003 The BBAN/National account number of the Originator AT-P003 The Proxy/Alias of the account of the Originator Either IBAN (AT-D001), BBAN/National Account number (AT-D003) or Proxy/Alias (AT-P003) need to be provided under Debtor account. AT-P003 can be populated in using Identification/Proxy or Identification/Scheme Name. The recommendation is to use Identification/Proxy. Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
2.65	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Either 'IBAN' or 'Other' should be populated. Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.66	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++IBAN	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type Pattern	<i>AT-D001 The IBAN of the account of the Originator.</i> IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
2.67	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-P003 The Proxy/Alias of the account of the Originator.</i> <i>AT-D003 The BBAN or National account number of the Originator</i> <i>When 'Proxy', 'Alias' or 'National account number/BBAN' is populated using 'Other', 'SchemeName' must be specified together with code (BBAN) or Proprietary code e.g. BGNR. 'Other' need to be included if proxy element is used.</i> Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1
2.68	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>If 'Proxy' or 'Alias' is provided in the Proxy element use 'NOTPROVIDED'.</i> Identification Identification assigned by an institution. Id Max34Text 1 .. 34 1 .. 34
2.69	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Scheme Name	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Proxy' or 'Alias' schemes defined by Proprietary code (e.g Swedish Bankgiro number, Swedish Plusgiro number etc). 'National account number/BBAN' defined with code (BBAN).</i> Scheme Name Name of the identification scheme. SchmeNm AccountSchemeName1Choice
	1..1		XML Tag	xs:choice
2.70	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Scheme Name ++++++Code	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Code used for National Account Number/BBAN.</i> Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalAccountIdentification1Code 1 .. 4 1 .. 4

#	NPC	Message Element	Customer to PSP Credit Transfer Information	
	Mult		NPC Core Requirements	
2.71	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Scheme Name ++++++Proprietary	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Proprietary code are used to define SchemeName. See message element specifications section 2.1.2.</i> Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.72	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Identification ++++Other +++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.73	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice
2.74	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Currency	ISO Name ISO Definition XML Tag Type Pattern	Currency Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.75	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.76	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-P003 The Proxy/Alias of the account of the of the Originator.</i> <i>"Sub-element 'Identification' is limited to 320 characters in length."</i> Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.77	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Type	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Either Code or Proprietary to be used</i> Type Type of the proxy identification. Tp ProxyAccountType1Choice
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.78	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Type +++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalProxyAccountType1Code 1 .. 4 1 .. 4
2.79	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Type +++++Proprietary	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary codes specifying the type of 'Alias' or 'Proxy' in AT-P003 (e.g. Swedish Bankgiro number, Swedish Plusgiro number etc). See message element specifications section 2.1.2. Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.80	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Account +++Proxy ++++Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	'Alias' or 'Proxy' defined by Code or Proprietary code (Swedish Bankgiro number, Swedish Plusgiro number etc). Identification Identification used to indicate the account identification under another specified name. Id Max2048Text 1 .. 2048 1 .. 320
2.81	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent	ISO Name ISO Definition XML Tag Type	Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
2.82	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either BICFI or 'Other/Identification' must be used. BICFI is recommended. Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstnId FinancialInstitutionIdentification18
2.83	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++BICFI	NPC Rulebook ISO Name ISO Definition XML Tag Type Pattern	AT-D002 The BIC code of the Originator PSP. BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}
2.84	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbId ClearingSystemMemberIdentification2
2.85	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identifier of the financial institution. LEI LEIIdentifier [A-Z0-9]{18,18}[0-9]{2,2}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.86	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
2.87	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.88	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1
2.89	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other +++++Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Only 'NOTPROVIDED' is allowed. Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
2.90	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other +++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
2.91	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Financial Institution Identification ++++Other +++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.92	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent +++Branch Identification	ISO Name ISO Definition XML Tag Type	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
2.93	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38

26 of 94

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.99	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Identification ++++Organisation Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' or 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.100	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Identification ++++Private Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.101	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.102	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Ultimate Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.103	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Charge Bearer	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	AT-T006 Charge bearer 'SHAR' or 'SLEV' to be used. It is recommended that this element is specified at 'Payment Information' level. Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code
			NPC Code Restrictions	
			SHAR	Shared Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor.
			SLEV	FollowingServiceLevel for NPC Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In addition, the full amount need to be credited to Beneficiary.
2.104	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Charges Account	ISO Name ISO Definition XML Tag Type	Charges Account Account used to process charges associated with a transaction. Usage: Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account. ChrgsAcct CashAccount38

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.105	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Charges Account Agent	ISO Name ISO Definition XML Tag Type	Charges Account Agent Agent that services a charges account. Usage: Charges account agent should only be used when the charges account agent is different from the debtor agent. ChrgsAcctAgt BranchAndFinancialInstitutionIdentification6
2.106	1..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information	ISO Name ISO Definition XML Tag Type	Credit Transfer Transaction Information Provides information on the individual transaction(s) included in the message. CdtTrfTxInf CreditTransferTransaction34
2.107	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification	ISO Name ISO Definition XML Tag Type	Payment Identification Set of elements used to reference a payment instruction. PmtId PaymentIdentification6
2.108	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification ++++Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Instruction Identification Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction. Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction. InstrId Max35Text 1 .. 35 1 .. 35
2.109	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification ++++End To End Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>AT-T014 The Originator's Reference of the NCT Inst Instruction.</i> End To End Identification Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. EndToEndId Max35Text 1 .. 35 1 .. 35
2.110	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Identification ++++UETR	ISO Name ISO Definition XML Tag Type Pattern	UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
2.111	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>'Payment Type Information' must be present either here or directly under 'Payment Information'.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfo26

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.112	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Instruction Priority	<i>NPC Usage Rule(s)</i>	If present, pre-agreed customer-to-PSP conditions apply. Based on whether priority processing vs. normal processing is offered by the PSP.
			ISO Name	Instruction Priority
			ISO Definition	Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.
			XML Tag	InstrPrty
			Type	Priority2Code
2.113	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Service Level	<i>NPC Usage Rule(s)</i>	Usage is recommended. Only one occurrence is allowed.
			ISO Name	Service Level
			ISO Definition	Agreement under which or rules under which the transaction should be processed.
			XML Tag	SvcLvl
			Type	ServiceLevel8Choice
	1..1		XML Tag	xs:choice
2.114	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Service Level +++++Code	<i>NPC Rulebook</i>	AT-T001 The identification code of the NPC Inst Scheme
			<i>NPC Usage Rule(s)</i>	Only 'NPCA' is allowed.
			ISO Name	Code
			ISO Definition	Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.
			XML Tag	Cd
			Type	ExternalServiceLevel1Code
			ISO Length	1 .. 4
			NPC Length	1 .. 4
			<i>NPC Code Restrictions</i>	
			NPCA	NordicPaymentsCouncilAreaTransfer Payments must be executed following the NPC Area Payment scheme.
2.115	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Service Level +++++Proprietary	ISO Name	Proprietary
			ISO Definition	Specifies a pre-agreed service or level of service between the parties, as a proprietary code.
			XML Tag	Prtry
			Type	Max35Text
			ISO Length	1 .. 35
			NPC Length	1 .. 35
2.116	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Local Instrument	ISO Name	Local Instrument
			ISO Definition	User community specific instrument.
				Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.
			XML Tag	LclInstrm
			Type	LocalInstrument2Choice
	1..1		XML Tag	xs:choice
2.117	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Local Instrument +++++Code	<i>NPC Usage Rule(s)</i>	Only 'INST' is allowed.
			ISO Name	Code
			ISO Definition	Specifies the local instrument, as published in an external local instrument code list.
			XML Tag	Cd
			Type	ExternalLocalInstrument1Code
			ISO Length	1 .. 35
			NPC Length	1 .. 35
			<i>NPC Code Restrictions</i>	
			INST	InstantCreditTransfer Transaction is related to an Instant Credit Transfer. Use case example: NPC Instant Credit Transfer (NCT Inst)

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.118	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Local Instrument +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Specifies the local instrument, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35
2.119	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Category Purpose	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T008 The category purpose of NCT Inst Instruction. If provided by the Originator the Originator PSP, must forward the 'Category Purpose' to the Beneficiary PSP. Category Purpose Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain. CtgyPurp CategoryPurpose1Choice
	1..1		XML Tag	xs:choice
2.120	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Category Purpose +++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Category purpose, as published in an external category purpose code list. Cd ExternalCategoryPurpose1Code 1 .. 4 1 .. 4
2.121	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Payment Type Information ++++Category Purpose +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Category purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.122	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.123	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Amount ++++Instructed Amount	NPC Rulebook NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	AT-T002 The amount of the NCT Inst in the relevant Scheme Currencies and the relevant currency code. Only 'Scheme Currencies' is allowed. Amount must be 0.01 or up to the maximum amount per instruction that can be processed under the Scheme as defined in document NPC014-01 Maximum Amount for Instructions under the NPC Instant Credit Transfer Scheme Rulebook or the maximum amount as agreed between individual Participants or communities of Participants. The fractional part has a maximum of two digits. Instructed Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Usage: This amount has to be transported unchanged through the transaction chain. InstdAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
2.124	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Amount ++++Equivalent Amount	ISO Name ISO Definition XML Tag Type	Equivalent Amount Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved. EqvtAmt EquivalentAmount2
2.125	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Exchange Rate Information	ISO Name ISO Definition XML Tag Type	Exchange Rate Information Provides details on the currency exchange rate and contract. XchgRateInf ExchangeRate1
2.126	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Charge Bearer	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T006 Charge bearer 'SHAR' or 'SLEV' to be used. It is recommended that this element be specified at 'Payment Information' level. Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code
			NPC Code Restrictions	
			SHAR	Shared Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor.
			SLEV	FollowingServiceLevel for NPC Transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In addition, the full amount need to be credited to Beneficiary.
2.127	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Cheque Instruction	ISO Name ISO Definition XML Tag Type	Cheque Instruction Set of elements needed to issue a cheque. ChqInstr Cheque11

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.128	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor	NPC Usage Rule(s)	Can be present on both payment and transaction level, if present transaction level will take precedence.
			ISO Name	Ultimate Debtor
			ISO Definition	Ultimate party that owes an amount of money to the (ultimate) creditor.
			XML Tag	UltmtDbtr
			Type	PartyIdentification135
2.129	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Name	NPC Rulebook	AT-P006 The name of the Originator Reference Party.
			NPC Usage Rule(s)	If Ultimate Debtor is used, name is mandatory.
			ISO Name	Name
			ISO Definition	Name by which a party is known and which is usually used to identify that party.
			XML Tag	Nm
			Type	Max140Text
			ISO Length	1 .. 140
			NPC Length	1 .. 140
2.130	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Postal Address	NPC Usage Rule(s)	STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address Line' is mandatory. UNSTRUCTURED ADDRESS: (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid address will be allowed - based on available information at the moment of publication). At least one occurrence of 'Address Line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP.
			ISO Name	Postal Address
			ISO Definition	Information that locates and identifies a specific address, as defined by postal services.
			XML Tag	PstlAdr
			Type	PostalAddress24
2.131	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Identification	NPC Rulebook	AT-P007 The identification code of the Originator Reference Party.
			ISO Name	Identification
			ISO Definition	Unique and unambiguous identification of a party.
			XML Tag	Id
			Type	Party38Choice
	1..1		XML Tag	xs:choice
2.132	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Identification +++++Organisation Identification	NPC Usage Rule(s)	Either 'AnyBIC', 'LEI' or 'Other' is allowed.
			ISO Name	Organisation Identification
			ISO Definition	Unique and unambiguous way to identify an organisation.
			XML Tag	OrgId
			Type	OrganisationIdentification29
2.133	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Identification +++++Private Identification	NPC Usage Rule(s)	Either 'Date and Place of Birth' or 'Other' is allowed.
			ISO Name	Private Identification
			ISO Definition	Unique and unambiguous identification of a person, for example a passport.
			XML Tag	PrvtId
			Type	PersonIdentification13

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.134	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.135	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Debtor ++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.136	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 1	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1 Agent between the debtor's agent and the creditor's agent. Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2. IntrmyAgt1 BranchAndFinancialInstitutionIdentification6
2.137	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 1Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1Account Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain. IntrmyAgt1Acct CashAccount38
2.138	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 2	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2 Agent between the debtor's agent and the creditor's agent. Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3. IntrmyAgt2 BranchAndFinancialInstitutionIdentification6
2.139	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 2Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2Account Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain. IntrmyAgt2Acct CashAccount38
2.140	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 3	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3 Agent between the debtor's agent and the creditor's agent. Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent. IntrmyAgt3 BranchAndFinancialInstitutionIdentification6
2.141	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Intermediary Agent 3Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3Account Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain. IntrmyAgt3Acct CashAccount38

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.142	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent	<i>NPC Usage Rule(s)</i>	Either BIC or Clearing system member identification to be used. Clearing system member identification is only allowed in combination with National Account Number or Alias/Proxy. If the BIC is not indicated 'Creditor Agent' structure is not to be used. Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
2.143	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification	<i>NPC Usage Rule(s)</i>	Either 'BIC' or 'Clearing system member Identification' must be used. Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstmId FinancialInstitutionIdentification18
2.144	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++BICFI	<i>NPC Rulebook</i> ISO Name ISO Definition	AT-C002 The BIC code of the Beneficiary PSP. BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}
2.145	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	Clearing system member identification is only allowed in combination with National Account Number or Alias/Proxy. Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbId ClearingSystemMemberIdentification2
2.146	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification +++++Clearing System Identification	ISO Name ISO Definition XML Tag Type	Clearing System Identification Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. ClrSysId ClearingSystemIdentification2Choice
	1..1		XML Tag	xs:choice
2.147	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification +++++Clearing System Identification +++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Identification of a clearing system, in a coded form as published in an external list. Cd ExternalClearingSystemIdentification1Code 1 .. 5 1 .. 5

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.148	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification ++++++Clearing System Identification +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Identification code for a clearing system, that has not yet been identified in the list of clearing systems. Prtry Max35Text 1 .. 35 1 .. 35
2.149	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification ++++++Member Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Member Identification Identification of a member of a clearing system. Mmbld Max35Text 1 .. 35 1 .. 35
2.150	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
2.151	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Creditor Party to which an amount of money is due. Cdtr PartyIdentification135
2.152	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Name	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-E001 The name of the Beneficiary. Mandatory. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140
2.153	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-E004 The address of the Beneficiary. STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address Line' is mandatory. UNSTRUCTURED ADDRESS: (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid address will be allowed - based on available information at the moment of publication). At least one occurrence of 'Address Line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.154	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice
2.155	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.156	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.157	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.158	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.159	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.160	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Floor	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.161	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.162	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Room	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.163	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16
2.164	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.165	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.166	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++District Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	District Name Identifies a subdivision within a country sub-division. DstrctNm Max35Text 1 .. 35 1 .. 35
2.167	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.168	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.169	0..2	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Postal Address +++++Address Line	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Up to two occurrences are allowed. Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.170	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-E005 The Beneficiary identification Code. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.171	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Identification +++++Organisation Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' or 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.172	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Identification +++++Private Identification	NPC Usage Rule(s)	Either 'Date and Place of Birth' or 'Other' is allowed.
			ISO Name	Private Identification
			ISO Definition	Unique and unambiguous identification of a person, for example a passport.
			XML Tag	PrvtId
			Type	PersonIdentification13
2.173	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Country Of Residence	ISO Name	Country Of Residence
			ISO Definition	Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.
			XML Tag	CtryOfRes
			Type	CountryCode
			Pattern	[A-Z]{2,2}
2.174	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor ++++Contact Details	ISO Name	Contact Details
			ISO Definition	Set of elements used to indicate how to contact the party.
			XML Tag	CtctDtls
			Type	Contact4
2.175	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account	NPC Rulebook	AT-C001 The IBAN of the account of the Beneficiary AT-C003 The BBAN/National account number of the Beneficiary AT-E003 The Proxy/Alias of the account of the Beneficiary.
			NPC Usage Rule(s)	Either IBAN (AT-C001), BBAN/National Account number (AT-C003) or Proxy/Alias (AT-E003) need to be provided under Creditor account. AT-E003 can be populated in using Identification/Proxy or Identification/Scheme Name. The recommendation is to use Identification/Proxy.
			ISO Name	Creditor Account
			ISO Definition	Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.
			XML Tag	CdtrAcct
			Type	CashAccount38
2.176	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification	NPC Usage Rule(s)	Mandatory. Either 'IBAN' or 'Other' should be populated.
			ISO Name	Identification
			ISO Definition	Unique and unambiguous identification for the account between the account owner and the account servicer.
			XML Tag	Id
			Type	AccountIdentification4Choice
	1..1		XML Tag	xs:choice
2.177	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++IBAN	NPC Rulebook	AT-C001 The IBAN of the account of the Beneficiary.
			ISO Name	IBAN
			ISO Definition	International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.
			XML Tag	IBAN
			Type	IBAN2007Identifier
			Pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.178	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> <i>AT-C003 The BBAN or National account number of the Beneficiary</i> <i>When 'Proxy', 'Alias' or 'National account number/BBAN' is populated using 'Other', 'SchemeName' must be specified together with code (BBAN) or Proprietary code e.g. BGNR. 'Other' need to be included if proxy element is used.</i> Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1
2.179	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>If 'Proxy' or 'Alias' is provided in the Proxy element use NOTPROVIDED.</i> Identification Identification assigned by an institution. Id Max34Text 1 .. 34 1 .. 34
2.180	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Scheme Name	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory if National Account Number (BBAN). Proxy' or 'Alias' schemes defined by Proprietary code (e.g Swedish Bankgiro number, Swedish Plusgiro number, Danish FIK/Giro). 'National account number/BBAN' defined with code (BBAN).</i> Scheme Name Name of the identification scheme. SchmeNm AccountSchemeName1Choice
	1..1		XML Tag	xs:choice
2.181	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Scheme Name +++++Code	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Code used for National Account Number/BBAN.</i> Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalAccountIdentification1Code 1 .. 4 1 .. 4
2.182	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Scheme Name +++++Proprietary	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Proprietary code are used to define SchemeName. See message element specifications section 2.1.2.</i> Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.183	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Identification +++++Other +++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.184	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice
2.185	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Currency	ISO Name ISO Definition XML Tag Type Pattern	Currency Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.186	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.187	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-E003 The Proxy/Alias of the account of the Beneficiary. "Sub-element 'Identification' is limited to 320 characters in length." Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.188	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy ++++Type	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either Code or Proprietary to be used Type Type of the proxy identification. Tp ProxyAccountType1Choice
	1..1		XML Tag	xs:choice
2.189	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy ++++Type ++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalProxyAccountType1Code 1 .. 4 1 .. 4

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.190	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy +++++Type ++++++Proprietary	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Proprietary codes specifying the type of 'Alias' or 'Proxy' in AT-E003 (e.g. Swedish Bankgiro number, Swedish Plusgiro number, Danish FIK Code etc). See message element specifications section 2.1.2.</i> Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text 1 .. 35 1 .. 35
2.191	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Creditor Account ++++Proxy +++++Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>'Alias' or 'Proxy' defined by Code or Proprietary code (e.g. Swedish Bankgiro number, Swedish Plusgironumber, Danish FIK Code etc).</i> Identification Identification used to indicate the account identification under another specified name. Id Max2048Text 1 .. 2048 1 .. 320
2.192	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr PartyIdentification135
2.193	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Name	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>If Ultimate Creditor is used, name is mandatory.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140
2.194	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Postal Address	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible.</i> <i>HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address Line' is mandatory.</i> <i>UNSTRUCTURED ADDRESS: (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid address will be allowed - based on available information at the moment of publication). At least one occurrence of 'Address Line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP.</i> Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information	
			NPC Core Requirements	
2.195	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Identification	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.196	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Identification +++++Organisation Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Either 'AnyBIC', 'LEI' or 'Other' is allowed .</i> Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.197	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Identification +++++Private Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Either 'Date and Place of Birth' or 'Other' is allowed.</i> Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.198	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.199	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Ultimate Creditor ++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.200	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Instruction For Creditor Agent	ISO Name ISO Definition XML Tag Type	Instruction For Creditor Agent Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent. InstrForCdtrAgt InstructionForCreditorAgent1
2.201	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Instruction For Debtor Agent	ISO Name ISO Definition XML Tag Type ISO Length <i>NPC Length</i>	Instruction For Debtor Agent Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent. InstrForDbtrAgt Max140Text 1 .. 140 1 .. 140
2.202	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Purpose	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of NCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.203	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Purpose ++++Code	<i>NPC Usage Rule(s)</i>	<i>In case the transaction is a transfer back related to an earlier executed NCT Inst Transaction, the purpose must be RRCT' (Reimbursement Received Credit Transfer) or another code meaningful for identifying the NCT Inst as a transfer back 'RRTP' (Related to an RTP) must be used if the NCT Inst is the result of a received Request-to-Pay message".</i>
			ISO Name ISO Definition	Code Underlying reason for the payment transaction, as published in an external purpose code list.
			XML Tag Type	Cd ExternalPurpose1Code
			ISO Length NPC Length	1 .. 4 1 .. 4
2.204	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.205	0..10	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.206	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.207	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7
2.208	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the NCT Inst Instruction.</i> <i>Either 'Structured' or 'Unstructured' may be present.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
2.209	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Unstructured	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>'Unstructured' may carry structured remittance information, as agreed between the Originator and the Beneficiary. Only one occurrence of 'Unstructured' is allowed.</i> Unstructured Information supplied to enable the matching/ reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Ustrd Max140Text 1 .. 140 1 .. 140

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.210	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured	NPC Usage Rule(s) Only one occurrence of 'Structured' is allowed. NPC Format Rule(s) 'Structured' can be used, provided the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) do not exceed 280 characters in length. ISO Name Structured ISO Definition Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. XML Tag Strd Type StructuredRemittanceInformation16	
2.211	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information	NPC Usage Rule(s) Only one occurrence is allowed. ISO Name Referred Document Information ISO Definition Provides the identification and the content of the referred document. XML Tag RfrdDocInf Type ReferredDocumentInformation7	
2.212	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type	ISO Name Type ISO Definition Specifies the type of referred document. XML Tag Tp Type ReferredDocumentType4	
2.213	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Code Or Proprietary	ISO Name Code Or Proprietary ISO Definition Provides the type details of the referred document. XML Tag CdOrPrtry Type ReferredDocumentType3Choice	
	1..1		XML Tag xs:choice	
2.214	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Code Or Proprietary +++++Code	NPC Usage Rule(s) Only CINV is allowed ISO Name Code ISO Definition Document type in a coded form. XML Tag Cd Type DocumentType6Code	
			NPC Code Restrictions	
			CINV	CommercialInvoice Document is an invoice.
2.215	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information +++++Type +++++Code Or Proprietary +++++Proprietary	ISO Name Proprietary ISO Definition Proprietary identification of the type of the remittance document. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 NPC Length 1 .. 35	

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.216	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information ++++++Type +++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Issuer Identification of the issuer of the reference document type. Issr Max35Text 1 .. 35 1 .. 35
2.217	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information ++++++Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Number Unique and unambiguous identification of the referred document. Nb Max35Text 1 .. 35 1 .. 35
2.218	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information ++++++Related Date	ISO Name ISO Definition XML Tag Type	Related Date Date associated with the referred document. RltdDt ISODate
2.219	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information ++++++Line Details	ISO Name ISO Definition XML Tag Type	Line Details Set of elements used to provide the content of the referred document line. LineDtls DocumentLineInformation1
2.220	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount	ISO Name ISO Definition XML Tag Type	Referred Document Amount Provides details on the amounts of the referred document. RfrdDocAmt RemittanceAmount2
2.221	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Due Payable Amount	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	Due Payable Amount Amount specified is the exact amount due and payable to the creditor. DuePyblAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99
2.222	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Discount Applied Amount	ISO Name ISO Definition XML Tag Type	Discount Applied Amount Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor. DscntApldAmt DiscountAmountAndType1
2.223	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Credit Note Amount	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	Credit Note Amount Amount specified for the referred document is the amount of a credit note. CdtNoteAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.224	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Tax Amount	ISO Name ISO Definition XML Tag Type	Tax Amount Quantity of cash resulting from the calculation of the tax. TaxAmt TaxAmountAndType1
2.225	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Adjustment Amount And Reason	ISO Name ISO Definition XML Tag Type	Adjustment Amount And Reason Specifies detailed information on the amount and reason of the document adjustment. AdjstmntAmtAndRsn DocumentAdjustment1
2.226	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount ++++++Remitted Amount	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	Remitted Amount Amount of money remitted for the referred document. RmtdAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 99999999999.99
2.227	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	When present, the Debtor PSP is obliged to validate the reference information. When used both 'Creditor Reference Type' and 'Creditor Reference' must be present. Creditor Reference Information Reference information provided by the creditor to allow the identification of the underlying documents. CdtrRefInf CreditorReferenceInformation2
2.228	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory if 'Creditor Reference Information' is used. Type Specifies the type of creditor reference. Tp CreditorReferenceType2
2.229	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice
	1..1		XML Tag	xs:choice
2.230	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary +++++++Code	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'SCOR' is allowed. Code Type of creditor reference, in a coded form. Cd DocumentType3Code
			NPC Code Restrictions	
			SCOR	StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.231	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.232	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Issuer	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	If RF/Structured Creditor Reference (ISO 11649) is used, type must be 'ISO'. Issuer Entity that assigns the credit reference type. Issr Max35Text 1 .. 35 1 .. 35
2.233	1..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Reference	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Mandatory if 'Creditor Reference Information' is used. When present, the Debtor PSP is obliged to validate the reference. Only OCR/KID Reference or RF/Structured Creditor Reference (ISO 11649) is allowed. RF/Structured Creditor Reference can only be used in combination with IBAN and must be used if 'ISO' is stated as 'Issuer'. OCR Reference can only be used in combination with a corresponding 'Proxy'/'Alias'. Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction. Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money. If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification. Ref Max35Text 1 .. 35 1 .. 35
2.234	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Invoicer	ISO Name ISO Definition XML Tag Type	Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor. Invr PartyIdentification135
2.235	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured +++++Invoicee	ISO Name ISO Definition XML Tag Type	Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor. Invcee PartyIdentification135

#	NPC Mult	Message Element	Customer to PSP Credit Transfer Information NPC Core Requirements	
2.236	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured ++++Tax Remittance	ISO Name ISO Definition XML Tag Type	Tax Remittance Provides remittance information about a payment made for tax-related purposes. TaxRmt TaxInformation7
2.237	0..1	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured ++++Garnishment Remittance	ISO Name ISO Definition XML Tag Type	Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes. GrnshmtRmt Garnishment3
2.238	0..3	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Remittance Information ++++Structured ++++Additional Remittance Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Remittance Information Additional information, in free text form, to complement the structured remittance information. AddtlRmtInf Max140Text 1 .. 140 1 .. 140
2.239	0..n	Customer Credit Transfer Initiation V09 +Payment Information ++Credit Transfer Transaction Information +++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
3.0	0..n	Customer Credit Transfer Initiation V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

2.1.2 Message Element Specifications

The list below contains proprietary codes to be used to identify one of the listed Alias or Proxies. These codes are not ISO codes. If other Alias or Proxies are used, a listed ISO code should be used, such as a mobile number.

For a full list of ISO 20022 visit the external code list page at www.ISO20022.org.

Code	Name	Description
DK71	FI payment card Type 71	Common Payment Card for all Danish Banks. In the code line these idents are present: Debtor, creditor, and payment identification. This makes automatic posting possible.
DK73	FI payment card Type 73	Common Payment Card for all Danish Banks. In the code line only creditor identification is present. Fields for the debtor's address and remittance advice are present
DK75	FI payment card Type 75	Common Payment Card for all Danish Banks. In the code line these idents are present: Debtor, creditor, and payment identification. This makes automatic posting possible. It is also possible to add remittance information.
DK01	Giro deposit card 01	Giro Payment Card. For payments to Danske Bank. In the code line only creditor identification is present. Fields for the debtor's address and remittance advice are present.
DK04	Giro deposit card 04	Giro Payment Card. For payments to Danske Bank. In the code line these Idents are present: Debtor, creditor, and payment identification. This makes automatic posting possible.
DK15	Giro deposit card 15	Giro Payment Card. For payments to Danske Bank. In the code line these idents are present: Debtor, creditor, and payment identification. This makes automatic posting possible.
BGNR	Bankgiro number	Bankgiro number is an Alias for a corporate account held in Sweden
PGNR	Plusgiro number	Plusgiro number is an Alias that could be used for corporate accounts held in Nordea Bank in Sweden

2.2 PSP to Customer Reject, Negative or Positive Confirmation (based on DS-03)

2.2.1 Recommended Use of the Customer Payment Status Report (pain.002.001.10)

A. Reject

The code 'RJCT' must be used in 'Group Status', or 'Payment Information Status' or 'Transaction Status'. The Originator PSP is the status originator and the reason code is different from 'timeout' related reasons.

The message caters for bulk and single reject messages.

Note: Attribute AT-R001 The type of "R" message in DS-03 is implied by the 'Message Name', 'pain.002.001.10', the 'Original Message Name Identification' set to 'pain.001.001.09' and 'Group Status', 'Payment Information Status' or 'Transaction Status' set to 'RJCT'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-01 attributes.

B. Negative confirmation

The code 'RJCT' must be used in 'Group Status', or 'Payment Information Status' or 'Transaction Status'. If the Originator PSP is the status originator (element 'Originator' under 'Status' on various levels) then the code has to be a time-out related reason. If the status originator is not the Originator PSP, then any status can be used.

The message caters for bulk and single negative confirmations.

Note: Attribute AT-R001 in DS-03 is implied by the 'Message Name', 'pain.002.001.10', the 'Original Message Name Identification' set to 'pain.001.001.09' and 'Group Status', 'Payment Information Status' or 'Transaction Status' set to 'RJCT'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

C. Positive confirmation

The code 'ACCP' (Accepted Customer Profile) or any other positive Status code must be used in 'Group Status', or 'Payment Information Status' or 'Transaction Status'.

The Beneficiary PSP is the 'Status Originator' (no reason code).

The message caters for bulk and single positive confirmations.

Examples of status codes to be used for each level are provided in this document in section 2.2.2 Message Specifications.

Note: The use case in DS-03 is implied by the 'Message Name', 'pain.002.001.10', the 'Original Message Name Identification' set to 'pain.001.001.09' and 'Group Status', 'Payment Information Status' or 'Transaction Status' set to 'ACCP' or to any other positive Status code.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Customer Payment Status Report V10	ISO Name ISO Definition	Customer Payment Status Report V10 Scope The CustomerPaymentStatusReport message is sent by an instructed agent to the previous party in the payment chain. It is used to inform this party about the positive or negative status of an instruction (either single or file). It is also used to report on a pending instruction. XML Tag Type CstmrPmtStsRpt CustomerPaymentStatusReportV10
1.0	1..1	Customer Payment Status Report V10 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the status report message. XML Tag Type GrpHdr GroupHeader86
1.1	1..1	Customer Payment Status Report V10 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party for a pre-agreed period. XML Tag Type MsgId Max35Text 1 .. 35 ISO Length NPC Length 1 .. 35
1.2	1..1	Customer Payment Status Report V10 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created. XML Tag Type CreDtTm ISODateTime
1.3	0..1	Customer Payment Status Report V10 +Group Header ++Initiating Party	NPC Usage Rule(s)	Used to identify a PSP (BICFI) as the sender of the message. Could also be used to identify the party who has initiated the original message. ISO Name ISO Definition Initiating Party Party that initiates the status message. XML Tag Type InitgPty PartyIdentification135
1.4	0..1	Customer Payment Status Report V10 +Group Header ++Forwarding Agent	ISO Name ISO Definition	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain. XML Tag Type FwdgAgt BranchAndFinancialInstitutionIdentification6
1.5	0..1	Customer Payment Status Report V10 +Group Header ++Debtor Agent	NPC Rulebook NPC Usage Rule(s)	AT-D002 The BIC code of the Originator PSP. Either BICFI or Clearing system member identification to be used. ISO Name ISO Definition Debtor Agent Financial institution servicing an account for the debtor. XML Tag Type DbtrAgt BranchAndFinancialInstitutionIdentification6
1.6	0..1	Customer Payment Status Report V10 +Group Header ++Creditor Agent	NPC Rulebook NPC Usage Rule(s)	AT-C002 The BIC code of the Beneficiary PSP. Either BICFI or Clearing system member Identification to be used. ISO Name ISO Definition Creditor Agent Financial institution servicing an account for the creditor. XML Tag Type CdtrAgt BranchAndFinancialInstitutionIdentification6

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
2.0	1..1	Customer Payment Status Report V10 +Original Group Information And Status	ISO Name ISO Definition XML Tag Type	Original Group Information And Status Original group information concerning the group of transactions, to which the status report message refers to. OrgnlGrpInfAndSts OriginalGroupHeader17
2.1	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Only pain.001.001.09 is allowed. Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime
2.4	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original message. OrgnlNbOfTxS Max15NumericText [0-9]{1,15}
2.5	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Original Control Sum	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original message, irrespective of currencies. OrgnlCtrlSum DecimalNumber 2 18
2.6	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Group Status	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R001 The type of "R" message. AT-R008 The status of the original message 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with a Code. See Message Element Specifications 2.1.2. Group Status Specifies the status of a group of transactions. GrpSts ExternalPaymentGroupStatus1Code 1 .. 4 1 .. 4
2.7	0..n	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	'Status Reason Information' must be present only if 'Group Status' is 'RJCT'. Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
2.8	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Originator	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	AT-R002 The identification of the type of party that initiated the "R" message (to be used for a negative confirmation or a reject) or AT-C002 The BIC code of the Beneficiary PSP (to be used for a positive confirmation). Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. Originator Party that issues the status. Orgtr PartyIdentification135
2.9	0..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	AT-R004 The reason code for non-acceptance of the NCT Inst Transaction. Mandatory if 'Group Status' is 'RJCT'. Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		XML Tag	xs:choice
2.10	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Code	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	See Message Element Specifications 2.1.3 below. Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4
2.11	1..1	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.12	0..n	Customer Payment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Information Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
2.13	0..n	Customer Payment Status Report V10 +Original Group Information And Status ++Number Of Transactions Per Status	ISO Name ISO Definition XML Tag Type	Number Of Transactions Per Status Detailed information on the number of transactions for each identical transaction status. NbOfTxPerSts NumberOfTransactionsPerStatus5
3.0	0..n	Customer Payment Status Report V10 +Original Payment Information And Status	ISO Name ISO Definition XML Tag Type	Original Payment Information And Status Information concerning the original payment information, to which the status report message refers. OrgnlPmtInfAndSts OriginalPaymentInstruction32
3.1	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnlPmtInfId Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.2	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original payment information group. OrgnlNbOfTxS Max15NumericText [0-9]{1,15}
3.3	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Original Control Sum	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original payment information group, irrespective of currencies. OrgnlCtrlSum DecimalNumber 2 18
3.4	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Payment Information Status	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R001 The type of "R" message. AT-R008 The status of the original message 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with a Code. See Message Element Specifications 2.1.2. Payment Information Status Specifies the status of the payment information group. PmtInfSts ExternalPaymentGroupStatus1Code 1 .. 4 1 .. 4
3.5	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory if 'Payment Information Status' is 'RJCT'. Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12
3.6	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Originator	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R002 The identification of the type of party that initiated the "R" message (to be used for a negative confirmation or a reject) or AT-C002 The BIC code of the Beneficiary PSP (to be used for a positive confirmation). Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. Originator Party that issues the status. Orgtr PartyIdentification135
3.7	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Reason	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R004 The reason code for non-acceptance of the NCT Inst Transaction. Mandatory if 'Group Status' is 'RJCT' (Rejected). Not allowed if 'Group Status' is 'ACCP' (Accepted Customer Profile). Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		XML Tag	xs:choice
3.8	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Reason ++++Code	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	See Message Element Specifications 2.1.3 below. Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.9	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
3.10	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Status Reason Information +++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Information Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.11	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Number Of Transactions Per Status	ISO Name ISO Definition XML Tag Type	Number Of Transactions Per Status Detailed information on the number of transactions for each identical transaction status. NbOfTxPerSts NumberOfTransactionsPerStatus5
3.12	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status	ISO Name ISO Definition XML Tag Type	Transaction Information And Status Provides information on the original transactions to which the status report message refers. TxInfAndSts PaymentTransaction105
3.13	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R003 The specific reference of the party initiating the reject (note: to be used for a negative confirmation or reject) or AT-T055 The Beneficiary PSP's reference of the NCT Inst Transaction (note: to be used for a positive confirmation). Status Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status. Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on. StsId Max35Text 1 .. 35 1 .. 35
3.14	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
3.15	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original End To End Identification	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-T014 The Originator's reference of the NCT Inst instruction. Mandatory. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.16	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
3.17	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Transaction Status	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-R001 The type of "R" message AT-R008 The status of the original message. 'Group Status', Payment Information Status' or 'Transaction Status' must be present with a Code. See Message Element Specifications 2.1.2 Transaction Status Specifies the status of a transaction, in a coded form. TxSts ExternalPaymentTransactionStatus1Code 1 .. 4 1 .. 4
3.18	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory if 'Transaction Status' is 'RJCT' (Rejected). Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12
3.19	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Originator	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R002 The identification of the type of party initiating the "R" message (to be used for a negative confirmation or a reject) or AT-C002 The BIC code of the Beneficiary PSP (to be used for a positive confirmation). Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. Originator Party that issues the status. Orgtr PartyIdentification135
3.20	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R004 The reason code for non-acceptance of the NCT Inst instruction. Mandatory if 'Transaction Status' is 'RJCT' (Rejected). Not allowed if 'Group Status' is 'ACCP' (Accepted Customer Profile). Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		XML Tag	xs:choice
3.21	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason +++++Code	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	See Message Element specifications 2.1.3 below. Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4
3.22	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.23	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Information Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.24	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges related to the processing of the rejection of the instruction. Usage: This is passed on for information purposes only. Settlement of the charges will be done separately. ChrgrsInf Charges7
3.25	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Tracker Data	ISO Name ISO Definition XML Tag Type	Tracker Data Provides information on the tracking of the interbank transaction related to the payment. TrckrData TrackerData1
3.26	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Acceptance Date Time	ISO Name ISO Definition XML Tag Type	Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcctncDtTm ISODateTime
3.27	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
3.28	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.29	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference	<p>NPC Rulebook An exact copy of attributes of the received DS-02 or DS-01 which is being rejected.</p> <p>NPC Usage Rule(s) The minimum requirement is the BICFI of the Debtor Agent. If used, other message elements must be populated with the same value as the message elements of the original instruction, within the following elements. Mandatory to provide Original Transaction Reference if transaction is rejected. Attributes as agreed between PSU and PSP must be included</p> <p>ISO Name Original Transaction Reference</p> <p>ISO Definition Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag OrgnlTxRef</p> <p>Type OriginalTransactionReference28</p>	
3.30	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	<p>ISO Name Interbank Settlement Amount</p> <p>ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag IntrBkSttlmAmt</p> <p>Type ActiveOrHistoricCurrencyAndAmount</p> <p>NPC FractDigits 2</p> <p>TotalDigits 18</p> <p>NPC Inclusive 0.01 .. 9999999999.99</p>	
3.31	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Amount	<p>NPC Rulebook AT-T002 The amount of the NCT Inst in the relevant Scheme Currencies and the relevant currency code.</p> <p>NPC Format Rule(s) Amount must be 0.01 or more and 9999999999.99 or less.</p> <p>ISO Name Amount</p> <p>ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Amt</p> <p>Type AmountType4Choice</p>	
3.32	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	<p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>	
3.33	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name Requested Collection Date</p> <p>ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag ReqdColltnDt</p> <p>Type ISODate</p>	
3.34	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	<p>NPC Rulebook AT-T013 The Requested Execution Date and Time of the NCT Inst Instruction.</p> <p>ISO Name Requested Execution Date</p> <p>ISO Definition Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag ReqdExctnDt</p> <p>Type DateAndDateTime2Choice</p>	

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.35	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.36	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.37	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	NPC Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 The identification code of the NCT Inst Scheme.</i> <i>AT-T008 The category purpose of the NCT Inst Instruction.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfo27
3.38	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
			NPC Code Restrictions	
			TRF	<i>CreditTransfer</i> <i>Transfer of an amount of money in the books of the account servicer.</i>
3.39	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.40	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	NPC Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the NCT Inst Instruction.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.41	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.42	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator identification code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.43	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> <i>AT-D003 The BBAN/National account number of the Originator</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.44	1..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP (if present in DS-01).</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.45	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.46	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP (if present in DS-01).</i> <i>Either BIC or Clearing system member Identification to be used.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.47	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.48	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> <i>Only 'Party' is allowed.</i> <i>Mandatory to provide Name if Creditor is used.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.49	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> <i>AT-C003 The BBAN/National account number of the Beneficiary</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38

#	NPC Mult	Message Element	PSP to Customer Reject, Positive or Negative Credit Transfer NPC Core Requirements	
3.50	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-E007 The name of the Beneficiary Reference Party. AT-E010 The identification code of the Beneficiary Reference Party. Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.51	0..1	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Purpose	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-T007 The purpose of the NCT Inst Instruction. Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.52	0..n	Customer Payment Status Report V10 +Original Payment Information And Status ++Transaction Information And Status +++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
4.0	0..n	Customer Payment Status Report V10 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

2.2.2 Message Element Specifications status code

The list below contains examples of ExternalPaymentGroupStatus1Code for “Group Status”:

ISO Code	ISO Name	Description of Status Code
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACTC	AcceptedTechnical Validation	Authentication and syntactical and semantical validation are successful.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

The list below contains examples of ExternalPaymentGroupStatus1Code for “Payment Information Status”:

ISO Code	ISO Name	Description of Status Code
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

The list below contains examples of ExternalPaymentTransactionStatus1Code for “Transaction Status”:

ISO Code	ISO Name	Description of Status Code
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACSC	AcceptedSettlementCompletedDebtorAccount	Settlement on the debtor's account has been completed.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
PDNG	Pending	Payment instruction is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

2.2.3 Message Element Specifications

The list below contains examples of reason codes to be used when a pain.002 message is used for other purposes than accepted. In addition to the code, for further clarification, information can be provided as Additional Information.

For a full list of ISO 20022 ExternalStatusReason1Code, visit the external code list page at www.ISO20022.org.

ISO Code	ISO Name	Description of Reason Code
AC01	IncorrectAccountNumber	Account identifier incorrect (i.e. invalid IBAN)
AC02	InvalidDebtorAccountNumber	Debtor account number invalid or missing
AC03	Invalid Creditor Account Number	Creditor account number invalid or missing
AC04	ClosedAccountNumber	Account closed
AC05	ClosedDebtorAccountNumber	Debtor account number closed
AC07	ClosedCreditorAccountNumber	Creditor account number closed
AC06	BlockedAccount	Account blocked, reason not specified
AG01	TransactionForbidden	Credit transfer forbidden on this type of account.
AG02	InvalidBankOperationCode	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for incorrect 'operation/transaction' code.
AM02	NotAllowedAmount	Amount exceeds the maximum authorised amount for NPC Inst
AM03	NotAllowedCurrency	Specified message amount is an non processable currency outside of existing agreement <i>Usage Rule:</i> To be used when Beneficiary PSP is not reachable in the specified currency.
AM04	Insufficient Funds	Amount of funds available to cover specified message amount is insufficient.
AM05	Duplication	Duplicate payment
AM11	InvalidTransactionCurrency	Transaction currency is invalid or missing <i>Usage Rule:</i> To be used when Beneficiary PSP is not reachable for cross border transactions.
BE04	MissingCreditorAddress	Account address is invalid
FF01	InvalidFileFormat	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for invalid file format.
MD07	EndCustomerDeceased	Beneficiary deceased
MS02	NotSpecifiedReasonCustomer Generated	By order of the Beneficiary
MS03	NotSpecifiedReasonAgentGenerated	Reason not specified
RC01	BankIdentifierIncorrect	PSP identifier incorrect (i.e. invalid BIC)
RR01	MissingDebtorAccountOrIdentification	Regulatory Reason
RR02	MissingDebtorsNameOrAddress	Regulatory Reason
RR03	MissingCreditorsNameOrAddress	Regulatory Reason

ISO Code	ISO Name	Description of Reason Code
RR04	RegulatoryReason	Regulatory Reason
RR05	RegulatoryInformationInvalid	Regulatory or Central Bank Reporting information missing, incomplete or invalid.
RR09	InvalidStructuredCreditorReference	Proprietary code for structured creditor reference invalid or missing. Usage rule: Used when structured reference is invalid or missing.
TM01	InvalidCutOffTime	Time-out – maximum execution time has been exceeded
DNOR	Debtor bank is not registered	Originator PSP is not registered under this BIC in the CSM
CNOR	Creditor bank is not registered	Beneficiary PSP is not registered under this BIC in the CSM

Following codes are specifically related to NCT Inst processing (e.g. time-out related codes):

ISO Code	ISO Name	NPC Core Reason
AB05	TimeoutCreditorAgent	Transaction stopped due to timeout at the Creditor Agent.
AB06	TimeoutInstructedAgent	Transaction stopped due to timeout at the Instructed Agent.
AB07	OfflineAgent	Agent of message is not online. Generic usage if it cannot be determined who exactly is not online.
AB08	OfflineCreditorAgent	Creditor Agent is not online.
AB09	ErrorCreditorAgent	Transaction stopped due to error at the Creditor Agent.
AB10	ErrorInstructedAgent	Transaction stopped due to error at the Instructed Agent.
AG10	AgentSuspended	Agent of message is suspended from the Real Time Payment system. Generic usage if it cannot be determined who exactly is suspended.
AG11	CreditorAgentSuspended	Creditor Agent of message is suspended from the Real Time Payment system.
AM23	AmountExceedsSettlementLimit	Transaction amount exceeds settlement limit.

2.3 Positive Notification Message to the Beneficiary (DS-10)

2.3.1 Use of the PSP-to-Customer Debit Credit Notification (camt.054.001.08)

The message is used to allow the Beneficiary PSP to inform the Beneficiary of a successfully executed NCT Inst Transaction.

The message caters for single positive credit notification message.

Note: The use case of the message is implied by 'Credit Debit Indicator' set to 'CRDT' (Credit) only, 'Entry', 'Entry Details' and 'Transaction Details' limited to one occurrence as well as 'Bank Transaction Code' set to 'PMNT RRCT ENCT'.

Note: The use of this message is recommended only. The Beneficiary PSP and Beneficiary can bilaterally agree to use this message or not.

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Bank To Customer Debit Credit Notification V08	ISO Name ISO Definition	Bank To Customer Debit Credit Notification V08 Scope The BankToCustomerDebitCreditNotification message is sent by the account servicer to an account owner or to a party authorised by the account owner to receive the message. It can be used to inform the account owner, or authorised party, of single or multiple debit and/or credit entries reported to the account. BkToCstmrDbtCdtNtfctn BankToCustomerDebitCreditNotificationV08
1.0	1..1	Bank To Customer Debit Credit Notification V08 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Common information for the message. GrpHdr GroupHeader81
1.1	1..1	Bank To Customer Debit Credit Notification V08 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the account servicing institution, and sent to the account owner or the party authorised to receive the message, to unambiguously identify the message. Usage: The account servicing institution has to make sure that MessageIdentification is unique per account owner for a pre-agreed period.
			XML Tag Type ISO Length NPC Length	MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Bank To Customer Debit Credit Notification V08 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	Bank To Customer Debit Credit Notification V08 +Group Header ++Message Recipient	ISO Name ISO Definition	Message Recipient Party authorised by the account owner to receive information about movements on the account. Usage: MessageRecipient should only be identified when different from the account owner.
			XML Tag Type	MsgRcpt PartyIdentification135
1.4	0..1	Bank To Customer Debit Credit Notification V08 +Group Header ++Message Pagination	ISO Name ISO Definition	Message Pagination Provides details on the page number of the message. Usage: The pagination of the message is only allowed when agreed between the parties.
			XML Tag Type	MsgPgntn Pagination1
1.5	0..1	Bank To Customer Debit Credit Notification V08 +Group Header ++Original Business Query	ISO Name ISO Definition	Original Business Query Unique identification, as assigned by the original requestor, to unambiguously identify the business query message.
			XML Tag Type	OrgnlBizQry OriginalBusinessQuery1
1.6	0..1	Bank To Customer Debit Credit Notification V08 +Group Header ++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Information Further details of the message. AddtlInf Max500Text 1 .. 500 1 .. 500

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.0	1..1	Bank To Customer Debit Credit Notification V08 +Notification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only one occurrence is allowed.</i> Notification Notifies debit and credit entries for the account. Ntfctn AccountNotification17
2.1	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Identification Unique identification, as assigned by the account servicer, to unambiguously identify the account notification. Id Max35Text 1 .. 35 1 .. 35
2.2	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Notification Pagination	ISO Name ISO Definition XML Tag Type	Notification Pagination Provides details on the page number of the notification. Usage: The pagination of the notification is only allowed when agreed between the parties. NtfctnPgntn Pagination1
2.3	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Electronic Sequence Number	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits	Electronic Sequence Number Sequential number of the notification, as assigned by the account servicer. Usage: The sequential number is increased incrementally for each notification sent electronically. ElectrncSeqNb Number 0 18
2.4	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Reporting Sequence	ISO Name ISO Definition XML Tag Type	Reporting Sequence Specifies the range of identification sequence numbers, as provided in the request. RptgSeq SequenceRange1Choice
2.5	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Legal Sequence Number	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits	Legal Sequence Number Legal sequential number of the notification, as assigned by the account servicer. It is increased incrementally for each notification sent. LglSeqNb Number 0 18
2.6	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the notification was created. CreDtTm ISODateTime
2.7	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++From To Date	ISO Name ISO Definition XML Tag Type	From To Date Range of time between a start date and an end date for which the account notification is issued. FrToDt DateTimePeriod1
2.8	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Copy Duplicate Indicator	ISO Name ISO Definition XML Tag Type	Copy Duplicate Indicator Indicates whether the document is a copy, a duplicate, or a duplicate of a copy. CpyDplctInd CopyDuplicate1Code
2.9	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Reporting Source	ISO Name ISO Definition XML Tag Type	Reporting Source Specifies the application used to generate the reporting. RptgSrc ReportingSource1Choice

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.10	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account	ISO Name ISO Definition XML Tag Type	Account Unambiguous identification of the account to which credit and debit entries are made. Acct CashAccount39
2.11	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-C001 The IBAN of the account of the Beneficiary. Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice
2.12	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice
2.13	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Currency	ISO Name ISO Definition XML Tag Type Pattern	Currency Identification of the currency in which the account is held. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.14	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.15	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Proxy	ISO Name ISO Definition XML Tag Type	Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.16	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Owner	ISO Name ISO Definition XML Tag Type	Owner Party that legally owns the account. Ownr PartyIdentification135
2.17	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Account +++Servicer	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-C002 The BIC code of the Beneficiary PSP. Only BICFI is allowed. If the BIC is not indicated 'Servicer' structure is not to be used. Servicer Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account. Svcr BranchAndFinancialInstitutionIdentification6

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.18	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Related Account	ISO Name ISO Definition XML Tag Type	Related Account Identifies the parent account of the account for which the notification has been issued. RltdAcct CashAccount38
2.19	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Interest	ISO Name ISO Definition XML Tag Type	Interest Provides general interest information that applies to the account at a particular moment in time. Intrst AccountInterest4
2.20	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Transactions Summary	ISO Name ISO Definition XML Tag Type	Transactions Summary Provides summary information on entries. TxSummry TotalTransactions6
2.21	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory</i> <i>Only one occurrence is allowed.</i> Entry Specifies an entry in the debit credit notification. Usage: At least one reference must be provided to identify the entry and its underlying transaction(s). Ntry ReportEntry10
2.22	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Reference	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Entry Reference Unique reference for the entry. NtryRef Max35Text 1 .. 35 1 .. 35
2.23	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Amount	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> <i>NPC Format Rule(s)</i> ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	<i>AT-T002 The amount of the NCT Inst in the relevant Scheme Currencies and the relevant currency code.</i> <i>Only 'NPC Scheme Currencies' is allowed.</i> <i>Amount must be 0.01 or up to the maximum amount per instruction that can be processed under the Scheme as defined in document NPC014-01 "Maximum Amount for Instructions under the NCT Inst Scheme Rulebook", or the maximum amount as agreed between individual Participants or communities of Participants.</i> <i>The fractional part has a maximum of two digits.</i> Amount Amount of money in the cash entry. Amt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 99999999999.99
2.24	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Credit Debit Indicator	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type <i>NPC Code Restrictions</i> <i>CRDT</i>	<i>AT-T081 The identification of the Credit Notification.</i> <i>Only 'CRDT' is allowed.</i> Credit Debit Indicator Indicates whether the entry is a credit or a debit entry. CdtDbtInd CreditDebitCode <i>Credit</i> <i>Operation is an increase.</i>

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.25	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Reversal Indicator	ISO Name ISO Definition XML Tag Type	Reversal Indicator Indicates whether or not the entry is the result of a reversal. Usage: This element should only be present if the entry is the result of a reversal. If the CreditDebitIndicator is CRDT and ReversalIndicator is Yes, the original operation was a debit entry. If the CreditDebitIndicator is DBIT and ReversalIndicator is Yes, the original operation was a credit entry. RvslInd TrueFalseIndicator
2.26	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Status	ISO Name ISO Definition XML Tag Type	Status Status of an entry on the books of the account servicer. Sts EntryStatus1Choice
	1..1		XML Tag	xs:choice
2.27	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Status ++++Code	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Only 'BOOK' or 'INFO' is allowed depending on a bilateral agreement between the Customer and its PSP. Code Entry status, in a coded form. Cd ExternalEntryStatus1Code 1 .. 4 1 .. 4
			NPC Code Restrictions	
			BOOK	Booked Booked means that the transfer of money has been completed between account servicer and account owner.
			INFO	Information Entry is only provided for information, and no booking on the account owner's account in the account servicer's ledger has been performed.
2.28	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Status ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Entry status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.29	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Booking Date	ISO Name ISO Definition XML Tag Type	Booking Date Date and time when an entry is posted to an account on the account servicer's books. Usage: Booking date is the expected booking date, unless the status is booked, in which case it is the actual booking date. BookgDt DateAndDateTime2Choice

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.30	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Value Date	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T082 The value date of the credit on the Beneficiary's account. Mandatory. Value Date Date and time at which assets become available to the account owner in case of a credit entry, or cease to be available to the account owner in case of a debit entry. Usage: If entry status is pending and value date is present, then the value date refers to an expected/requested value date. For entries subject to availability/float and for which availability information is provided, the value date must not be used. In this case the availability component identifies the number of availability days. ValDt DateAndDateTime2Choice
	1..1		XML Tag	xs:choice
2.31	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Value Date ++++Date	ISO Name ISO Definition XML Tag Type	Date Specified date. Dt ISODate
2.32	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Value Date ++++Date Time	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only UTC time format or local time with UTC offset format can be used. Date Time Specified date and time. DtTm ISODateTime
2.33	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Account Servicer Reference Unique reference as assigned by the account servicing institution to unambiguously identify the entry. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
2.34	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Availability	ISO Name ISO Definition XML Tag Type	Availability Indicates when the booked amount of money will become available, that is can be accessed and starts generating interest. Usage: This type of information is used in the US and is linked to particular instruments such as cheques. Example: When a cheque is deposited, it will be booked on the deposit day, but the amount of money will only be accessible as of the indicated availability day (according to national banking regulations). Avlbt CashAvailability1
2.35	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	The identification code of the NCT Inst Scheme Bank Transaction Code Set of elements used to fully identify the type of underlying transaction resulting in an entry. BkTxCd BankTransactionCodeStructure4

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.36	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code ++++Domain	ISO Name Domain ISO Definition Set of elements used to provide the domain, the family and the sub-family of the bank transaction code, in a structured and hierarchical format. Usage: If a specific family or sub-family code cannot be provided, the generic family code defined for the domain or the generic sub-family code defined for the family should be provided. XML Tag Domn Type BankTransactionCodeStructure5	
2.37	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code ++++Domain +++++Code	NPC Usage Rule(s) Only "PMNT" is allowed. ISO Name Code ISO Definition Specifies the business area of the underlying transaction. XML Tag Cd Type ExternalBankTransactionDomain1Code ISO Length 1 .. 4 NPC Length 1 .. 4 NPC Code Restrictions PMNT Payments The Payments domain provides the bank transaction codes for all payment activities that relate to transfer of funds between parties.	
2.38	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code ++++Domain +++++Family	ISO Name Family ISO Definition Specifies the family and the sub-family of the bank transaction code, within a specific domain, in a structured and hierarchical format. XML Tag Fmly Type BankTransactionCodeStructure6	
2.39	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code ++++Domain +++++Family ++++++Code	NPC Usage Rule(s) Only "RRCT" is allowed. ISO Name Code ISO Definition Specifies the family within a domain. XML Tag Cd Type ExternalBankTransactionFamily1Code ISO Length 1 .. 4 NPC Length 1 .. 4 NPC Code Restrictions RRCT Received Real-Time Credit Transfers Receivable Real Time Credit Transfers are instructions to receive an amount of money from a debtor by the account owner in Real Time (within a pre-agreed number of seconds). The receivable credit transfers are related to transactions received by the account owner.	
2.40	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code ++++Domain +++++Family ++++++Sub Family Code	NPC Usage Rule(s) Only "ENCT" is allowed. ISO Name Sub Family Code ISO Definition Specifies the sub-product family within a specific family. XML Tag SubFmlyCd Type ExternalBankTransactionSubFamily1Code ISO Length 1 .. 4 NPC Length 1 .. 4 NPC Code Restrictions ENCT Nordic Payment Council Credit Transfer Transaction is a nordic payment council credit transfer	

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.41	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Bank Transaction Code ++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Bank transaction code in a proprietary form, as defined by the issuer. Prtry ProprietaryBankTransactionCodeStructure1
2.42	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Commission Waiver Indicator	ISO Name ISO Definition XML Tag Type	Commission Waiver Indicator Indicates whether the transaction is exempt from commission. ComssnWvrInd YesNoIndicator
2.43	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Additional Information Indicator	ISO Name ISO Definition XML Tag Type	Additional Information Indicator Indicates whether the underlying transaction details are provided through a separate message, as in the case of aggregate bookings. AddtlInfInd MessageIdentification2
2.44	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Amount Details	ISO Name ISO Definition XML Tag Type	Amount Details Provides information on the original amount. Usage: This component (on entry level) should be used when a total original batch or aggregate amount has to be provided. If required, the individual original amounts can be included in the same component on transaction details level. AmtDtls AmountAndCurrencyExchange3
2.45	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Charges	ISO Name ISO Definition XML Tag Type	Charges Provides information on the charges, pre-advised or included in the entry amount. Usage: This component is used on entry level in case of batch or aggregate bookings. Chrgs Charges6
2.46	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Technical Input Channel	ISO Name ISO Definition XML Tag Type	Technical Input Channel Channel used to technically input the instruction related to the entry. TechInptChanl TechnicalInputChannel1Choice
2.47	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Interest	ISO Name ISO Definition XML Tag Type	Interest Provides details of the interest amount included in the entry amount. Usage: This component is used on entry level in the case of batch or aggregate bookings. Intrst TransactionInterest4
2.48	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Card Transaction	ISO Name ISO Definition XML Tag Type	Card Transaction Provides details of the card transaction included in the entry amount, when globalised by the account servicer. CardTx CardEntry4
2.49	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory. Only one occurrence is allowed.</i> Entry Details Provides details on the entry. NtryDtls EntryDetails9

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.50	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Batch	ISO Name ISO Definition XML Tag Type	Batch Provides details on batched transactions. Btch BatchInformation2
2.51	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory. Only one occurrence is allowed.</i> Transaction Details Provides information on the underlying transaction(s). TxDtls EntryTransaction10
2.52	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References	ISO Name ISO Definition XML Tag Type	References Provides the identification of the underlying transaction. Refs TransactionReferences6
2.53	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Message Identification Point to point reference, as assigned by the instructing party of the underlying message. MsgId Max35Text 1 .. 35 1 .. 35
2.54	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
2.55	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Payment Information Identification Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message. PmtInfId Max35Text 1 .. 35 1 .. 35
2.56	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Instruction Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction. Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction. InstrId Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.57	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++End To End Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-T014 The Originator's reference of the NCT Inst Instruction. End To End Identification Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain. EndToEndId Max35Text 1 .. 35 1 .. 35
2.58	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++UETR	ISO Name ISO Definition XML Tag Type Pattern	UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
2.59	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Transaction Identification Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain. Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period. TxId Max35Text 1 .. 35 1 .. 35
2.60	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Mandate Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Mandate Identification Unique identification, as assigned by the creditor, to unambiguously identify the mandate. MndtId Max35Text 1 .. 35 1 .. 35
2.61	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Cheque Number	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Cheque Number Unique and unambiguous identifier for a cheque as assigned by the agent. ChqNb Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.62	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain. ClrSysRef Max35Text 1 .. 35 1 .. 35
2.63	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Account Owner Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Account Owner Transaction Identification Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account). AcctOwnrTxId Max35Text 1 .. 35 1 .. 35
2.64	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Account Servicer Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Account Servicer Transaction Identification Unambiguous identification of the securities transaction as known by the securities account servicer. AcctSvcrTxId Max35Text 1 .. 35 1 .. 35
2.65	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Market Infrastructure Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Market Infrastructure Transaction Identification Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities. MktInfrstrctrTxId Max35Text 1 .. 35 1 .. 35
2.66	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Processing Identification	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Processing Identification Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure. PrcgId Max35Text 1 .. 35 1 .. 35
2.67	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++References ++++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Proprietary reference related to the underlying transaction. Prtry ProprietaryReference1
2.68	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Amount	ISO Name ISO Definition XML Tag Type NPC FractDigits TotalDigits NPC Inclusive	Amount Amount of money in the cash transaction. Amt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 9999999999.99

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.69	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Credit Debit Indicator	ISO Name ISO Definition XML Tag Type	Credit Debit Indicator Indicates whether the transaction is a credit or a debit transaction. CdtDbtInd CreditDebitCode
2.70	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Amount Details	ISO Name ISO Definition XML Tag Type	Amount Details Provides detailed information on the original amount. Usage: This component (on transaction level) should be used in case booking is for a single transaction and the original amount is different from the entry amount. It can also be used in case individual original amounts are provided in case of a batch or aggregate booking. AmtDtls AmountAndCurrencyExchange3
2.71	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Availability	ISO Name ISO Definition XML Tag Type	Availability Indicates when the booked amount of money will become available, that is can be accessed and starts generating interest. Usage: This type of information is used in the US and is linked to particular instruments such as cheques. Example: When a cheque is deposited, it will be booked on the deposit day, but the amount of money will only be accessible as of the indicated availability day (according to national banking regulations). Avlbtty CashAvailability1
2.72	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Bank Transaction Code	ISO Name ISO Definition XML Tag Type	Bank Transaction Code Set of elements used to fully identify the type of underlying transaction resulting in an entry. BkTxCd BankTransactionCodeStructure4
2.73	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Charges	ISO Name ISO Definition XML Tag Type	Charges Provides information on the charges, pre-advised or included in the entry amount. Usage: This component (on transaction level) can be used in case the booking is for a single transaction, and charges are included in the entry amount. It can also be used in case individual charge amounts are applied to individual transactions in case of a batch or aggregate amount booking. Chrgs Charges6

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.74	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Interest	ISO Name ISO Definition XML Tag Type	Interest Provides details of the interest amount included in the entry amount. Usage: This component (on transaction level) can be used if the booking is for a single transaction, and interest amount is included in the entry amount. It can also be used if individual interest amounts are applied to individual transactions in the case of a batch or aggregate amount booking. Intrst TransactionInterest4
2.75	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties	ISO Name ISO Definition XML Tag Type	Related Parties Set of elements used to identify the parties related to the underlying transaction. RltdPties TransactionParties6
2.76	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties +++++Initiating Party	ISO Name ISO Definition XML Tag Type	Initiating Party Party that initiated the payment that is reported in the entry. InitgPty Party40Choice
2.77	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties +++++Debtor	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory. Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
	1..1		XML Tag	xs:choice
2.78	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties +++++Debtor +++++Party	ISO Name ISO Definition XML Tag Type	Party Identification of a person or an organisation. Pty PartyIdentification135
2.79	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties +++++Debtor +++++Party +++++Name	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length <i>NPC Length</i>	<i>AT-P001 The name of the Originator.</i> <i>Mandatory.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.80	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Party +++++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.81	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Party +++++++Identification	NPC Rulebook ISO Name ISO Definition XML Tag Type	AT-P004 The Originator identification code Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.82	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Party +++++++Identification +++++++Organisation Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.83	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Party +++++++Identification +++++++Private Identification	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.84	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Party +++++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.85	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Party +++++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.86	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor +++++++Agent	ISO Name ISO Definition XML Tag Type	Agent Identification of a financial institution. Agt BranchAndFinancialInstitutionIdentification6
2.87	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Debtor Account	ISO Name ISO Definition XML Tag Type	Debtor Account Unambiguous identification of the account of the debtor. DbtrAcct CashAccount38
2.88	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
	1..1		XML Tag	xs:choice
2.89	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party	ISO Name ISO Definition XML Tag Type	Party Identification of a person or an organisation. Pty PartyIdentification135
2.90	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Name	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>AT-P006 The name of the Originator Reference Party.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140
2.91	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.92	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Identification	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-P007 The identification code of the Originator Reference Party</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.93	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Identification +++++++Organisation Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.94	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Identification +++++++Organisation Identification +++++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identification as an alternate identification for a party. LEI LEIIdentifier [A-Z0-9]{18,18}[0-9]{2,2}
			This element is not part of the NPC Core subset	
2.95	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Identification +++++++Private Identification	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.96	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.97	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Party +++++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.98	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Debtor +++++++Agent	ISO Name ISO Definition XML Tag Type	Agent Identification of a financial institution. Agt BranchAndFinancialInstitutionIdentification6
2.99	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory. Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
	1..1		XML Tag	xs:choice
2.100	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Party	ISO Name ISO Definition XML Tag Type	Party Identification of a person or an organisation. Pty PartyIdentification135
2.101	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Party +++++++Name	<i>NPC Rulebook</i> <i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>AT-E001 The name of the Beneficiary.</i> <i>Mandatory.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140
2.102	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Party +++++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.103	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Party +++++++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification of a party. Id Party38Choice
2.104	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Party +++++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.105	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Party +++++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.106	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor +++++++Agent	ISO Name ISO Definition XML Tag Type	Agent Identification of a financial institution. Agt BranchAndFinancialInstitutionIdentification6
2.107	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Creditor Account	ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry has been posted as a result of the payment transaction. CdtrAcct CashAccount38
2.108	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties +++++++Ultimate Creditor	<i>NPC Usage Rule(s)</i> Only 'Party' is allowed. ISO Name ISO Definition XML Tag Type	
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.109	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Party	ISO Name ISO Definition XML Tag Type	Party Identification of a person or an organisation. Pty PartyIdentification135
2.110	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Party +++++++Name	NPC Rulebook ISO Name ISO Definition XML Tag Type ISO Length NPC Length	AT-E007 The name of the Beneficiary Reference Party. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140
2.111	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Party +++++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.112	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Party +++++++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification of a party. Id Party38Choice
2.113	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Party +++++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.114	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Party +++++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.115	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Ultimate Creditor +++++++Agent	ISO Name ISO Definition XML Tag Type	Agent Identification of a financial institution. Agt BranchAndFinancialInstitutionIdentification6
2.116	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Trading Party	ISO Name ISO Definition XML Tag Type	Trading Party Party that plays an active role in planning and executing the transactions that create or liquidate investments of the investors assets, or that move the investor's assets from one investment to another. A trading party is a trade instructor, an investment decision-maker, a post trade administrator, or a trader. In the context of treasury, it is the party that negotiates and executes the treasury transaction. TradgPty Party40Choice
2.117	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Parties ++++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Proprietary party related to the underlying transaction. Prtry ProprietaryParty5
2.118	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Agents	ISO Name ISO Definition XML Tag Type	Related Agents Set of elements used to identify the agents related to the underlying transaction. RltdAgts TransactionAgents5
2.119	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Local Instrument	ISO Name ISO Definition XML Tag Type	Local Instrument User community specific instrument. Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level. LclInstrm LocalInstrument2Choice
2.120	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Purpose	<i>NPC Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the NCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
	1..1		XML Tag	xs:choice

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.121	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Purpose ++++++Code	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Code Underlying reason for the payment transaction, as published in an external purpose code list. Cd ExternalPurpose1Code 1 .. 4 1 .. 4
2.122	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Purpose ++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.123	0..10	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7
2.124	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information	NPC Rulebook NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the NCT Inst Instruction. Either 'Structured' or 'Unstructured' may be present Remittance Information Structured information that enables the matching, that is reconciliation, of a payment with the items that the payment is intended to settle, such as commercial invoices in an account receivable system. RmtInf RemittanceInformation16
2.125	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Unstructured	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	'Unstructured' may carry structured remittance information, as agreed between the Originator and the Beneficiary. Only one occurrence of 'Unstructured' is allowed. Unstructured Information supplied to enable the matching/ reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Ustrd Max140Text 1 .. 140 1 .. 140
2.126	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured	NPC Usage Rule(s) NPC Format Rule(s) ISO Name ISO Definition XML Tag Type	Only one occurrence of 'Structured' is allowed. 'Structured' can be used, provided the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) do not exceed 280 characters in length. Structured Information supplied to enable the matching/ reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. Strd StructuredRemittanceInformation16

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.127	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Referred Document Information	ISO Name ISO Definition XML Tag Type	Referred Document Information Provides the identification and the content of the referred document. RfrdDocInf ReferredDocumentInformation7
2.128	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Referred Document Amount	ISO Name ISO Definition XML Tag Type	Referred Document Amount Provides details on the amounts of the referred document. RfrdDocAmt RemittanceAmount2
2.129	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>When present, the Debtor Bank is not obliged to validate the reference information. When used both 'Type' and 'Reference' must be present.</i> Creditor Reference Information Reference information provided by the creditor to allow the identification of the underlying documents. CdtrRefInf CreditorReferenceInformation2
2.130	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information +++++++Type	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory if 'Creditor Reference Information' is used.</i> Type Specifies the type of creditor reference. Tp CreditorReferenceType2
2.131	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information +++++++Type +++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice
	1..1		XML Tag	xs:choice
2.132	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information +++++++Type +++++++Code Or Proprietary +++++++Code	<i>NPC Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only 'SCOR' is allowed.</i> Code Type of creditor reference, in a coded form. Cd DocumentType3Code

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
			NPC Code Restrictions	
			SCOR	<i>StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.</i>
2.133	1..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information +++++++Type +++++++Code Or Proprietary +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.134	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information +++++++Type +++++++Issuer	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Mandatory if 'Reference' is populated with an identifier issued or governed by a known institution. E.g. "ISO" should be mentioned here if 'Reference' is populated with a RF/Structured Creditor Reference (ISO 11649)."</i> Issuer Entity that assigns the credit reference type. Issr Max35Text 1 .. 35 1 .. 35
2.135	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Creditor Reference Information +++++++Reference	NPC Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length NPC Length	<i>Mandatory if 'Creditor Reference Information' is used. If a Creditor Reference contains a check digit, the receiving PSP is not required to validate this. If the receiving PSP validates the check digit and if this validation fails, the PSP may continue its processing and send the transaction to the next party in the chain. RF/Structured Creditor Reference must be used (ISO 11649) in case "ISO" is mentioned under 'issuer'.</i> Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction. Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money. If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification. Ref Max35Text 1 .. 35 1 .. 35

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.136	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Invoicer	ISO Name ISO Definition XML Tag Type	Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor. Invcr PartyIdentification135
2.137	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Invoicee	ISO Name ISO Definition XML Tag Type	Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor. Invcee PartyIdentification135
2.138	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Tax Remittance	ISO Name ISO Definition XML Tag Type	Tax Remittance Provides remittance information about a payment made for tax-related purposes. TaxRmt TaxInformation7
2.139	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Garnishment Remittance	ISO Name ISO Definition XML Tag Type	Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes. GrnshmtRmt Garnishment3
2.140	0..3	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Remittance Information ++++++Structured +++++++Additional Remittance Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Remittance Information Additional information, in free text form, to complement the structured remittance information. AddtlRmtInf Max140Text 1 .. 140 1 .. 140
2.141	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Dates	ISO Name ISO Definition XML Tag Type	Related Dates Set of elements used to identify the dates related to the underlying transactions. RltdDts TransactionDates3
2.142	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Price	ISO Name ISO Definition XML Tag Type	Related Price Set of elements used to identify the price information related to the underlying transaction. RltdPric TransactionPrice4Choice

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.143	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Related Quantities	ISO Name ISO Definition XML Tag Type	Related Quantities Set of elements used to identify the related quantities, such as securities, in the underlying transaction. RltdQties TransactionQuantities3Choice
2.144	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Financial Instrument Identification	ISO Name ISO Definition XML Tag Type	Financial Instrument Identification Identification of a security, as assigned under a formal or proprietary identification scheme. FinInstrmId SecurityIdentification19
2.145	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.146	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Return Information	ISO Name ISO Definition XML Tag Type	Return Information Provides the return information. RtrInf PaymentReturnReason5
2.147	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Corporate Action	ISO Name ISO Definition XML Tag Type	Corporate Action Set of elements used to identify the underlying corporate action. CorpActn CorporateAction9
2.148	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Safekeeping Account	ISO Name ISO Definition XML Tag Type	Safekeeping Account Safekeeping or investment account. A safekeeping account is an account on which a securities entry is made. An investment account is an account between an investor(s) and a fund manager or a fund. The account can contain holdings in any investment fund or investment fund class managed (or distributed) by the fund manager, within the same fund family. SfkpgAcct SecuritiesAccount19
2.149	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Cash Deposit	ISO Name ISO Definition XML Tag Type	Cash Deposit Provides the details of a cash deposit for an amount of money in cash notes and/or coins. CshDpst CashDeposit1
2.150	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Card Transaction	ISO Name ISO Definition XML Tag Type	Card Transaction Provides the data related to the card (number, scheme), terminal (number, identification) and transactional data used to uniquely identify a card transaction. CardTx CardTransaction17

#	NPC Mult	Message Element	PSP to Customer Credit Notification NPC Core Requirements	
2.151	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Additional Transaction Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Transaction Information Further details of the transaction. AddtlTxInf Max500Text 1 .. 500 1 .. 500
2.152	0..n	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Entry Details ++++Transaction Details +++++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
2.153	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Entry +++Additional Entry Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Entry Information Further details of the entry. AddtlNtryInf Max500Text 1 .. 500 1 .. 500
2.154	0..1	Bank To Customer Debit Credit Notification V08 +Notification ++Additional Notification Information	ISO Name ISO Definition XML Tag Type ISO Length NPC Length	Additional Notification Information Further details of the account notification. AddtlNtfctnInf Max500Text 1 .. 500 1 .. 500
3.0	0..n	Bank To Customer Debit Credit Notification V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

3. List of changes in the NPC Instant Credit Transfer Customer-to-PSP Implementation Guidelines 2025 version 1.0

(Note: This list is for information – the changes included in the body of the document are the changes in effect)

SYMBOLS USED

1. Column one contains the identification number of the Change
2. Column two contains the reference(s) to the relevant Index Number
3. Column three contains the reference(s) to the relevant section or message element
4. Column four contains a description of the change
5. Column five contains a status code:
 - REJ: Rejected by the NCT & NCT Inst WG
 - PEN: Issue pending in the NCT & NCT Inst WG
 - ACC: Accepted by the NCT & NCT Inst WG in Guidelines
6. Column six contains the type of change:
 - TYPO: Typing and layout errors
 - CLAR: Clarification of the text
 - CHAN: Change in or further alignment with the Rulebook content

3.1 List of changes 2025 v 1.0 relative to 2023 v 1.3

N°	#	Section / Message Element	Description	Status	Type
1.	General		Attribute numbering changed from AT-XX to AT-XNNN throughout the document.	ACC	CHAN
2.	General		All name elements changed from max 70 characters to max 140 characters. NPC format rule: 'Name is limited to 70 characters in length' removed.	ACC	CHAN
3.	1.5.3		Sentence "For ease of use, National Account Number will be treated as an Alias, too" removed.	ACC	CLAR
4.	1.5.4		The text in this section is modified due to CR #03 New attribute for BBAN and National account number.	ACC	CHAN
5.	2.1.1		Text in the last Note bullet 2 changed since alternative 1 is preferred. Som modification in text to be correct.	ACC	CLAR
6.	2.1.1		New Note added in the end of the section to clarify usage of the new attribute for BBAN and National account number.	ACC	CHAN
7.	2.1.1	2.23	Usage Rule in Debtor – Postal Address changed	ACC	CHAN
8.	2.1.1	2.39	Usage Rule in Debtor – Postal Address – Address Line changed	ACC	CHAN

N°	#	Section / Message Element	Description	Status	Type
9.	2.1.1	2.48	Usage Rule added in Debtor – Identification – Organization Identification – Other – Scheme Name – Proprietary	ACC	CHAN
10.	2.1.1	2.64	Added attribute and updated Usage Rule in Debtor Account	ACC	CHAN
11.	2.1.1	2.65	Changed Usage Rule in Debtor Account – Identification	ACC	CHAN
12.	2.1.1	2.67	New attribute added	ACC	CHAN
13.	2.1.1	2.71	Usage Rule updated referring to message element specifications added	ACC	CLAR
14.	2.1.1	2.73	Type changed to white	ACC	CHAN
15.	2.1.1	2.75	Name changed to white	ACC	CHAN
16.	2.1.1	2.76	Attribute and Usage Rule added in Debtor Account – Proxy	ACC	CHAN
17.	2.1.1	2.79	Added reference to section 2.1.2 in Debtor Account – Proxy – Type – Proprietary Usage Rule	ACC	CHAN
18.	2.1.1	2.97	Usage Rule in Ultimate Debtor – Postal Address changed	ACC	CHAN
19.	2.1.1	2.103	Added attribute in Charge Bearer	ACC	CHAN
20.	2.1.1	2.110	UETR changed to yellow	ACC	CHAN
21.	2.1.1	2.126	Added attribute in Charge Bearer	ACC	CHAN
22.	2.1.1	2.130	Usage Rule in Ultimate Debtor – Postal Address changed	ACC	CHAN
23.	2.1.1	2.153	Usage Rule in Creditor – Postal Address changed	ACC	CHAN
24.	2.1.1	2.169	Usage Rule in Creditor – Address Line changed	ACC	CHAN
25.	2.1.1	2.175	Added attribute and Usage Rule in Creditor Account	ACC	CHAN
26.	2.1.1	2.176	Changed Usage Rule in Creditor Account - Identification	ACC	CHAN
27.	2.1.1	2.178	New attribute added	ACC	CHAN
28.	2.1.1	2.184	Type changed to white	ACC	CHAN
29.	2.1.1	2.186	Name changed to white	ACC	CHAN
30.	2.1.1	2.187	Attribute and Usage Rule added in Creditor Account – Proxy	ACC	CHAN
31.	2.1.1	2.190	Added reference to section 2.1.2 in Creditor Account – Proxy – Type – Proprietary Usage Rule	ACC	CHAN
32.	2.1.1	2.193	Made name mandatory and added Usage Rule	ACC	CHAN
33.	2.1.1	2.194	Usage Rule in Ultimate Creditor – Postal Address changed	ACC	CHAN
34.	2.1.1	2.210	Format rule in Remittance Information – Structured changed from 140 to 280	ACC	CHAN
35.	2.1.2		New section added with a list of proprietary codes used for Alias and Proxy.	ACC	CLAR
36.	2.2.1		“or any other positive Status code” added in text under bullet C and new text referring to 2.2.2 added.	ACC	CHAN
37.	2.2.1	1.3	Usage Rule changed in Initiation Party	ACC	CHAN
38.	2.2.1	2.6	Attribute added to Group Status	ACC	CHAN
39.	2.2.1	2.10	Changed from 2.2.3 to 2.1.3 in Rulebook text	ACC	TYPO
40.	2.2.1	3.4	Attribute added to Payment Information Status	ACC	CHAN
41.	2.2.1	3.8	Changed from 2.2.3 to 2.1.3 in Rulebook text	ACC	TYPO

N°	#	Section / Message Element	Description	Status	Type
42.	2.2.1	3.17	Attribute added to Transaction Status	ACC	CHAN
43.	2.2.1	3.21	Changed from 2.2.3 to 2.1.3 in Rulebook text	ACC	TYPO
44.	2.2.1	3.29	Added text in Usage Rule in Original Transaction Reference	ACC	CHAN
45.	2.2.1	3.43	Added attribute in Debtor Account	ACC	CHAN
46.	2.2.1	3.49	Added attribute in Creditor Account	ACC	CHAN
47.	2.2.2		New section 2.2.2. added with a list of examples for Status codes. Section 2.2.3 is now the list with examples with reason codes.	ACC	CHAN
48.	2.3.1	2.58	UETR made yellow	ACC	CHAN
49.	2.3.1	2.126	Format rule in Remittance Information – Structured changed from 140 to 280	ACC	CHAN